

PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

LED BR Lamps G3

BR20, BR30, BR40 Series



7W BR20



8W BR30
11W BR30



12W BR40
17W BR40

Product Description

With a full array of BR lamps, MaxLite products offer an immediate payback with LED replacements for 50-, 65-, 75-, and 100-watt incandescent lamps. Available in a standard medium base, the LED BR lamp is an ideal lighting solution for track lights, display lights and recessed lights. They provide efficient, general lighting suited for architectural, residential, retail, office space and hospitality applications.

Features

- 120V, 60Hz
- 25,000 hour life (at L70 standards)
- CRI: ≥ 80
- BR lens conceals LEDs from sight and evenly distributes the light
- Smooth aluminum housing with ANSI standard form factor
- Dimmable down to ten percent
- Operating temperature: -4°F to 104°F
- Suitable for use in damp locations
- Not for use in enclosed luminaires

Warranty

5 years. Check maxlite.com/warranties for details.

Compatible Dimmers

BRAND	MODEL NUMBER	BRAND	MODEL NUMBER
Lutron	CTCL-153P	Leviton	IPL06
	DVCL-153P		IP110
	LGCL-153P		6631-LW
	S-600		6683-IW

Ordering Information

FAMILY	DIMMIBILITY	CCT
7BR20 = 7 Watts, BR20 8BR30 = 8 Watts, BR30 11BR30 = 11 Watts, BR30 12BR40 = 12 Watts, BR40 17BR40 = 17 Watts, BR40	DLED = Dimmable	27/G3 = 2700K 30/G3 = 3000K 40/G3 = 4000K 50/G3 = 5000K*

* 5000K model only available for 8BR30DLED50/G3

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received, including interference that may cause undesired operation.

LED Desk Lamp

Specifications

	BR20	BR30		BR40	
Wattage	7W	8W	11W	12W	75
Color Temperature	2700K, 3000K, 4000K	2700K, 3000K, 4000K, 5000K	2700K, 3000K, 4000K	2700K, 3000K, 4000K	2700K, 3000K, 4000K
Lumens Delivered (lm)	550 lm	650 lm	850 lm	1,050 lm	1,400 lm
Efficacy (lm/W)	79 lm/W	81 lm/W	77 lm/W	88 lm/W	82 lm/W
Equivalency	50W	65W	65W	75W	100W
Lumen Maintenance (L70)	25,000 hours				
Power Factor	≥ 0.70				
Input Voltage	120V				
Operating Temperature	-4°F to 104°F				
Environment	Dry, Damp				
Warranty	5 years. Check maxlite.com/warranties for details.				

Compatible Dimmers

ORDER CODE	MODEL NUMBER	WATTAGE	INCANDESCENT EQUIVALENT	CRI	OUTPUT (LUMENS)	DIMENSIONS HxW	CCT
BR20							
14099046	7BR20DLED27/G3	7W	50W	82	550	3.8" x 2.5"	2700K
14099047	7BR20DLED30/G3	7W	50W	82	550	3.8" x 2.5"	3000K
14099048	7BR20DLED40/G3	7W	50W	84	550	3.8" x 2.5"	4000K
BR30							
14099049	8BR30DLED27/G3	8W	65W	80	650	5.12" x 3.74"	2700K
14099050	8BR30DLED30/G3	8W	65W	80	650	5.12" x 3.74"	3000K
14099051	8BR30DLED40/G3	8W	65W	80	650	5.12" x 3.74"	4000K
14099657	8BR30DLED50/G3	8W	65W	80	650	5.12" x 3.74"	5000K
14099421	11BR30DLED27/G3	11W	65W	82	850	5.12" x 3.74"	2700K
14099423	11BR30DLED30/G3	11W	65W	82	850	5.12" x 3.74"	3000K
14099424	11BR30DLED40/G3	11W	65W	84	850	5.12" x 3.74"	4000K
BR40							
14099052	12BR40DLED27/G3	12W	75W	82	1050	6.25" x 4.75"	2700K
14099053	12BR40DLED30/G3	12W	75W	84	1050	6.25" x 4.75"	3000K
14099054	12BR40DLED40/G3	12W	75W	84	1050	6.25" x 4.75"	4000K
14099418	17BR40DLED27/G3	17W	100W	82	1400	6.25" x 4.75"	2700K
14099419	17BR40DLED30/G3	17W	100W	82	1400	6.25" x 4.75"	3000K
14099420	17BR40DLED40/G3	17W	100W	84	1400	6.25" x 4.75"	4000K