

PROJECT NAME: \_\_\_\_\_ CAT. #: \_\_\_\_\_  
 NOTES: \_\_\_\_\_ FIXTURE SCHEDULE: \_\_\_\_\_

## LED PLL - Bypass, Coated Glass, UL, Type B



### Specifications

Specifications	17PLLBxx-CG		
Power Consumption (W)	17W		
Lumens Delivered (lm)	2,150 lm	2,200 lm	2,200 lm
Color Temperature (CCT)	3500K	4000K	5000K
Efficacy	127 lm/W	130 lm/W	130 lm/W
CRI	≥ 80		
Lumen Maintenance (L70)	50,000 Hours		
Power Factor	≥ 0.90		
Input Voltage	120V-277V, 50/60 Hz		
Operating Temperature	-4°F to 104°F		
Lens	Opal (Frosted) - PET Coated Glass		
Weight (lbs)	0.38lbs		
Certification	UL Classified, UL UR, FCC		
Material Usage	RoHS compliant; no mercury		
Environment	Dry & Damp, Enclosed Fixtures		
Warranty	5 Year warranty. Check <a href="http://maxlite.com/warranties">maxlite.com/warranties</a> for details.		

### Product Description

The LED PLL Lamp is the easy way to upgrade downlights and commercial luminaires to the energy-saving benefits of LED via a simple ballast bypass. A seamless replacement for 40-watt CFL tubes, the LED lamp consumes 50 percent less energy and lasts twice as long as its fluorescent counterpart.

### Features

- Type-B (Ballast Bypass)
- 120-277V
- ≥ 80 CRI
- CCT: 3500,4000,5000
- Power factor ≥ 0.90
- 2G11 Base
- UL Classified (Type-B)
- Suitable for enclosed fixtures
- Frosted PET COATED Glass construction
- 5 year warranty

### Ordering Structure

WATTAGE	FAMILY	COLOR	CCT, LENS, BASE
17 = 17W	PLL = PLL Series	B = Ballast Bypass	<b>35-CG</b> = 3500K, PET Coated Glass, 2G11 <b>40-CG</b> = 4000K, PET Coated Glass, 2G11 <b>50-CG</b> = 5000K, PET Coated Glass, 2G11

#### NOTES:

1. This device is not intended for use with emergency exits or for emergency lighting
2. Do not use with dimmers

### Stocked Items - DLC 5.1 Listing

ORDER CODE	ITEM NUMBER	DLC PRODUCT ID#	DLC CLASSIFICATION	DLC PRIMARY USE DESIGNATION
14100787	17PLL35-CG	PLVYJ7OZNSJ	Standard	Internal Driver/Line Voltage (UL Type B) Lamps
14100788	17PLL40-CG	PLP2PPU4BEOP		
14100789	17PLL50-CG	PLG6UYFV6AKJ		