

**LED HIGH OUTPUT  
NON-DIMMABLE  
OMNIDIRECTIONAL A-LAMP**  
A21 and A23 SERIES



26A23



21A21



17A21



**PRODUCT DESCRIPTION:**

MaxLite's LED High Output Non Dimmable Omnidirectional A-Line lamp replicate true A21 and A23 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces, table and floor lamps.

**FEATURES:**

- 17W, 2,000lm, 125W Inc. replacement
- 21W, 2,600lm, 150W Inc. replacement
- 26W, 3,000-3,200lm, 200W Inc. replacement
- ENERGY STAR certified for 17W and 21W only
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- Volts: 120-277V Universal
- Suitable for damp locations

**APPLICATIONS**

- Pendants
- Table and floor lamps
- Sconces

**WARRANTY:**

5-year standard warranty (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))  
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

**ORDERING:**

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 17A21ND27	
FAMILY	BASE	DIMMABILITY	CCT
<b>17A21=</b> 17 watts, A21 <b>21A21=</b> 21 watts, A21 <b>26A23=</b> 26 watts, A23	(OMIT)= E26	ND= Non-Dimmable	<b>27=</b> 2700K <b>30=</b> 3000K <b>40=</b> 4000K <b>50=</b> 5000K

**SPECIFICATIONS:**

ITEM	SPECIFICATION	DETAILS		
		17A21NDxx	21A21NDxx	26A23NDxx
<b>GENERAL PERFORMANCE</b>	Power Consumption	17W	21W	26W
	Lumens Delivered	2000	2600	3,000-3,200
	Efficacy (lm/w)	118	118	116-123
	CRI	≥80		
	Color Temperature (CCT)	2700K, 3000K, 4000K, 5000K		
	Lumen Maintenance (L70)	25,000 Hours		
<b>ELECTRICAL</b>	Power Factor	≥0.95		
	Input Voltage	120-277V Universal		
<b>PHYSICAL</b>	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
<b>CERTIFICATION</b>	Certification	UL Listed, Energy Star, FCC		UL Listed, FCC
	Environment	Damp		
	Warranty	5 Year standard warranty*		

**ORDERING:**

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
<b>E26 Base</b>									
102733	17A21ND27	★	17	125W Inc.	2000	118	80	2700K	2.55" x 4.92"
102734	17A21ND30	★	17	125W Inc.	2000	118	80	3000K	
102735	17A21ND40	★	17	125W Inc.	2000	118	80	4000K	
102736	17A21ND50	★	17	125W Inc.	2000	118	80	5000K	
102729	21A21ND27	★	21	150W Inc.	2600	118	80	2700K	2.75" x 5.13"
102730	21A21ND30	★	21	150W Inc.	2600	118	80	3000K	
102731	21A21ND40	★	21	150W Inc.	2600	118	80	4000K	
102732	21A21ND50	★	21	150W Inc.	2600	118	80	5000K	
102725	26A23ND27		26	200W Inc.	3000	116	80	2700K	3.15" x 5.90"
102726	26A23ND30		26	200W Inc.	3200	123	80	3000K	
102727	26A23ND40		26	200W Inc.	3200	123	80	4000K	
102728	26A23ND50		26	200W Inc.	3200	123	80	5000K	

★ ENERGY STAR Certified

Specifications are subject to change without notice.