

DISC LIGHT CCT SELECTABLE SERIES



DL6



DL7

PRODUCT DESCRIPTION:

The LED Disc Light's versatility as a flush mount fixture and surface downlight saves electrical contractors time, labor and space by making it possible to install custom downlighting without a recessed can. This luminaire is wet location rated, CCT selectable (2700K/3000K/4000K/5000K), Title 20 and ETL listed as both a retrofit kit and a luminaire. The slim-profile Disc Light is available in two sizes, and mounts directly to a 3"/4"/5"/6" housing and standard 4" J-Box. In other words, more options and fewer SKUs to stock on distributor shelves and job sites!

Providing exceptional performance in general lighting applications for homes, hotels, motels and commercial properties, this series can also serve as a cost-effective temporary lighting solution. The luminaire is the ideal choice for adding energy-efficient and long-lasting downlighting to bathrooms, showers, spas and other indoor wet, damp, dry locations environment.



FEATURES:

- E26 screw-base connector included
- Listed as a fixture and a retrofit
- Tested and listed with Lutron

DIMMING:

- 120V option available with 120V triac dimming (10%)

MOUNTING:

- DL6 model fits 3"/4" housing and standard 4" J-Box
- DL7 model fits 3"/4"/5"/6" housing and standard 4" J-Box
- E26 screw-base connector included

CONSTRUCTION:

- Durable thermoplastic housing
- Plastic lens

LISTINGS:

- ETL listed for Wet Locations, Indoor
- T20 Listed
- Supports T24 Part 6 high efficacy lighting requirements
- JA8 Listed for CCTs ≥ 4000K

WARRANTY:

5-year standard warranty (further details available at www.maxlite.com/warranties)

ORDERING STRUCTURE

FAMILY	SIZE	WATTAGE (NOMINAL)	CRI	CCT	FINISH
DL= Disc Light	6= O.D. 5.20"	07= 07W	9= 90	CS= 2700K/3000K/4000K/5000K CCT Selectable (Default CCT set to 2700K)	WH= White
	7= O.D. 7.33"	11= 11W			

ORDER CODE

ORDER CODE	MODEL NUMBER
103864	DL6079CSWH
103873	DL7119CSWH

COMPATIBLE DIMMERS

DIMMER BRAND	MODELS
LUTRON	DVLV-600P, DVLEV-303P, DV-600P, MACL-153M, SCL-153P, DVCL-153P, MAELV-600, CTCL-153PDH-WH, TGCL-153PH-WH, DVWCL-153PH-WH

SPECIFICATIONS

	DL6079CSWH	DL7119CSWH
	DETAILS	
Nominal Wattage (W)	7W	11W
Lumens Delivered (lm)	650	1000
Equivalency	40W INC	75W INC
Efficacy (lm/W)	97	95
Beam Angle	110°	
CRI	≥90	
Color Temperature (K)	CCT Selectable: 2700K, 3000K, 4000K, 5000K (Default CCT set to 2700K)	
L70 Lifetime (Hrs)	≥50,000 Hrs	
Voltage	120V, Triac Dimming, 10%	
Power Factor	≥0.90	
Housing	Thermoplastic	
Lens	Plastic	
Mounting	3/4" housings, 4"J-box	3/4"/5/6" housings, 4"J-box
Operating Temperature	-4°F to 104°F	
Listings	JA8, Title 24, Title 20, cETLus, FCC	
Environment	Wet locations, Indoor	
Warranty	5 Years	

PRODUCT DIMENSIONS:

