

LED ROUGH SERVICE A-LAMPS
A19 NON-DIM ROUGH SERVICE SERIES



9W



14W



PRODUCT DESCRIPTION:

MaxLite's LED Rough Service A-Line lamps replicate the function of a Rough Service Incandescent lamp that produces even light in areas that are subject to vibration and lamp impact. They are suited for a wide variety of commercial and residential applications including most garage door openers, manufacturing operations and warehouses.

FEATURES:

- 9 Watts (60W Equivalent, 800 Lumens)
- 14 Watts (100W Equivalent, 1500 Lumens)
- 11,000 hour life (L70 standards)
- CCT: 3000K
- CRI: ≥ 80
- Non-Dimmable
- Enclosed rated
- Saves more than 84 percent on energy
- Power factor: ≥ 0.6
- Standard E26 base
- Mercury-free
- RoHS Compliant
- One year limited warranty
- Suitable for enclosed fixtures
- Vibration and impact resistant
- Shatter proof
- Works with most garage door openers- No RF interference

APPLICATIONS

- Table and floor lamps
- Industrial Lighting
- Garage door openers
- Sconces
- Approved for use in fully enclosed luminaires
- Suitable for use in damp locations

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example:		
LAMP	BASE	DIMMABILITY	CCT	FAMILY
E9A19= Enclosed, 9 Watts, A19 E14A19= Enclosed, 14 Watts, A19	(OMIT)= E26	NDV= Non-Dimmable Value	30= 3000K	RS= Rough Service

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference.
 (2) This device must accept any interference received, including interference that may cause undesired operation.

SPECIFICATIONS:

SPECIFICATIONS:		E9A19NDV30RS	E14A19NDV30RS
ITEM	SPECIFICATION	DETAILS	
GENERAL PERFORMANCE	Power Consumption	9W	14W
	Lumens Delivered	800	1,500
	Efficacy (lm/w)	89	107
	CRI	≥80	
	Color Temperature (CCT)	3000K	
	Lumen Maintenance (L70)	11,000 Hours	
	Dimmable	No	
ELECTRICAL	Power Factor	≥0.80	
	Input Voltage	120V	
PHYSICAL	Base Type	E26	
	Operating Temperature	-4°F - 104°F	
CERTIFICATION	Environment	Dry, Damp	
	Warranty	1 Year Limited	

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL NUMBER	INPUT WATTAGE	EQUIVALENT WATTAGE	DELIVERED LUMENS	EFFICACY (LM/W)	CRI	CCT (K)	DIMENSIONS (D" x MOL")
102611	E9A19NDV30RS	9	60W Inc.	800	94	80	3000K	2.36" x 4.76"
102406	E14A19NDV30RS	14	100W Inc.	1,500	107	80	3000K	2.36" x 4.76"

Specifications are subject to change without notice.