

PROJECT NAME: \_\_\_\_\_ CAT. #: \_\_\_\_\_  
 NOTES: \_\_\_\_\_ FIXTURE SCHEDULE: \_\_\_\_\_

## Enclosed Non-Dim High Output A Lamps



17W

20W

26W

### Features:

- Suitable for use in Enclosed Rated Luminaires and Recessed Luminaires
- Suitable for dry and damp location

### Application:

- Pendants
- Table and floor lamps
- Scones

### Application:

- UL Listed for Dry/Damp locations

### Warranty:

5 years standard. Click here for details on 10-year warranty.

[www.maxlite.com/warranties](http://www.maxlite.com/warranties)

## Ordering Information

WATTAGE & FAMILY	DIMMABILITY	COLOR TEMPERATURE
<b>E16.5A21</b> = Enclosed Rated 16.5 Watt, A21 Lamp	ND=Non-Dimmable	<b>27</b> = 2700K
<b>E20A21</b> = Enclosed Rated 20 Watt, A21 Lamp		<b>30</b> = 3000K
<b>E24PS25</b> = Enclosed Rated 24 Watt, PS25 Lamp		<b>40</b> = 4000K <b>50</b> = 5000K

## Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR #
105249	E16.5A21ND27	2368923
105250	E16.5A21ND30	2368924
105251	E16.5A21ND40	2368925
105252	E16.5A21ND50	2368926
105253	E20A21ND30	2368927
105254	E20A21ND40	2368928
105255	E20A21ND50	2368929
105256	E24PS25ND30	2368940
105257	E24PS25ND40	2368941
105258	E24PS25ND50	2368942

## Enclosed Non-Dim High Output A Lamps

### Specifications

	E16.5A21NDxx	E20A21NDxx	E24S25NDxx
Nominal Wattage (W)	16.5W	20W	24W
Lumens Delivered	2000 lm	2600 lm	3200 lm
Equivalency	125W INC	150W INC	200W INC
Efficacy (lm/W)	118 lm/w	130 lm/w	133 lm/w
Beam Angle		230°	
CRI		≥80	
CCT (K)		2700K, 3000K, 4000K, 5000K	
L70 Lifetime (hrs)		≥25,000 Hrs	
Voltage		120-277V, 50/60Hz	
Power Factor		≥0.9	
Operating Temperature		-4°F to 104°F (-20°C to 40°C)	
Listings		Energy Star, cULus, FCC, RoHS Compliant	
Environment		UL Listed for Dry/Damp Location	
Detection angle		5 Year Warranty	

### Dimensions

