

LED OMNIDIRECTIONAL A-LAMP
ENCLOSED RATED A-LAMP
JA8 SERIES



5W, 9W & 12W



17W



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescent. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

FEATURES:

- 5W, 450lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 12W, 1100lm, 75W Inc. replacement
- 17W, 1600lm, 100W Inc. replacement
- Dimmable down to 10 percent
- Power factor: ≥ 0.90
- 25,000 hour life (L70 standards)
- CRI: ≥ 90
- Supports Compliance of JA8-2016-E
- Supports Compliance of CEC Title 20
- Suitable for dry and damp locations
- Suitable in fully enclosed luminaires

APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces

WARRANTY:

5-year standard warranty
(further details available at www.maxlite.com/warranties)
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: E9A19D927/JA8	
		D	JA8
E5A19= 5 watts, A19		D= Dimmable	JA8= Supports compliance of JA8-2016-E
E9A19= 9 watts, A19			
E12A19= 12 watts, A19		927= 2700K	
E17A21= 17 watts, A21		930= 3000K	
		950= 5000K	

*ENERGY STAR Certification is in progress and pending

SPECIFICATIONS:

ITEM	SPECIFICATION	DETAILS			
		E5A19D9xx/JA8	E9A19D9xx/JA8	E12A19D9xx/JA8	E17A21D9xx/JA8
GENERAL PERFORMANCE	Power Consumption	5W	9W	12W	17W
	Lumens Delivered	450	800	1100	1600
	Efficacy (lm/w)	90	88	91	94
	CRI	≥90			
	Color Temperature (CCT)	2700K, 3000K, 5000K			
	Lumen Maintenance (L70)	25,000 Hours			
ELECTRICAL	Power Factor	≥0.9			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Certification	RoHS Compliant			
	Environment	Dry, Damp, Enclosed, JA8-2016-E			
	Warranty	5 year warranty			

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
14099798	E5A19D927/JA8	★	5	40W Inc.	450	90	92	2700K	2.36" x 4.25"
14099799	E5A19D930/JA8	★	5	40W Inc.	450	90	92	3000K	
14100790	E5A19D950/JA8	★	5	40W Inc.	450	90	92	5000K	
14099800	E9A19D927/JA8	★	9	60W Inc.	800	88	92	2700K	
14099801	E9A19D930/JA8	★	9	60W Inc.	800	88	92	3000K	
14100791	E9A19D950/JA8	★	9	60W Inc.	800	88	92	5000K	
14099802	E12A19D927/JA8	★	12	75W Inc.	1100	91	92	2700K	
14099803	E12A19D930/JA8	★	12	75W Inc.	1100	91	92	3000K	
14100792	E12A19D950/JA8	★	12	75W Inc.	1100	91	92	5000K	
14099804	E17A21D927/JA8	★	17	100W Inc.	1600	94	92	2700K	2.36" x 5.42"
14099805	E17A21D930/JA8	★	17	100W Inc.	1600	94	92	3000K	
14100793	E17A21D950/JA8	★	17	100W Inc.	1600	94	92	5000K	

★ ENERGY STAR Pending

Specifications are subject to change without notice.

COMPATIBLE DIMMERS (E5A19D99XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	603-6631-A
	6631
	6631-A
	6631-LA
	6672
	6683
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
	LUTRON
AYCL-153PH	
DVCL-153P-WH	
DVWCL-153PH-WHC	
S-603PH-WH	
SCL-153PH-WH	
TGCL-153PH-WH	
MEW-DM600	
MAXXIMA	MEW-DM600

COMPATIBLE DIMMERS (E9A19D9XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
	LUTRON
AYCL-153PH	
DVCL-153P-WH	
DVWCL-153PH-WHC	
S-603PH-WH	
SCL-153PH-WH	
TGCL-153PH-WH	
MEW-DM600	
MAAXXIMA	MEW-DM600

COMPATIBLE DIMMERS (E12A19D9XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6631-LA
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DVWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAXXIMA	MEW-DM600

COMPATIBLE DIMMERS (E17A21D99XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	6631
	603-6631-A
	6631-A
	6631-LA
LUTRON	AYCL-153P-WH
	AYCL-153PH
	D-600PH-DK
	D-600R-IV
	DV-600P-WH
	DV-600PH-WH
	DV-603P
	DV-603PH-WH
	DV-603PR
	DVW-600PH-WH
	MACL-153M-WH
	MACL-153MLH-WH
	MACL-153MR-WH
	MACL-153MH-WH
	S-600
	S-600-AL
	S-600P-WH
	S-603PH-WH
TG-600PH-IV	
TGCL-153PH-WH	

Specifications are subject to change without notice.