

**LED ROUGH SERVICE A-LAMPS**  
A19 NON-DIM ROUGH SERVICE SERIES



9W



14W



**PRODUCT DESCRIPTION:**

MaxLite's LED Rough Service A-Line lamps replicate the function of a Rough Service Incandescent lamp that produces even light in areas that are subject to vibration and lamp impact. They are suited for a wide variety of commercial and residential applications including most garage door openers, manufacturing operations and warehouses.

**FEATURES:**

- 9 Watts (60W Equivalent, 800 Lumens)
- 14 Watts (100W Equivalent, 1500 Lumens)
- 11,000 hour life (L70 standards)
- CCT: 3000K
- CRI:  $\geq 80$
- Non-Dimmable
- Enclosed rated
- Saves more than 84 percent on energy
- Power factor:  $\geq 0.6$
- Standard E26 base
- Mercury-free
- RoHS Compliant
- One year limited warranty
- Suitable for enclosed fixtures
- Vibration and impact resistant
- Shatter proof
- Works with most garage door openers- No RF interference

**APPLICATIONS**

- Table and floor lamps
- Industrial Lighting
- Garage door openers
- Sconces
- Approved for use in fully enclosed luminaires
- Suitable for use in damp locations

**ORDERING:**

| MODEL SELECTION (Full list of order codes on pg. 2)                            |                    | Typical order example:         |                  |                          |
|--|--------------------|--------------------------------|------------------|--------------------------|
| LAMP   | BASE               | DIMMABILITY                    | CCT              | FAMILY                   |
| <b>E9A19=</b> Enclosed, 9 Watts, A19<br><b>E14A19=</b> Enclosed, 14 Watts, A19 | <b>(OMIT)=</b> E26 | <b>NDV=</b> Non-Dimmable Value | <b>30=</b> 3000K | <b>RS=</b> Rough Service |

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
 (1) This device may not cause harmful interference.  
 (2) This device must accept any interference received, including interference that may cause undesired operation.

**SPECIFICATIONS:**

| SPECIFICATIONS:     |                         | E9A19NDV30RS   | E14A19NDV30RS |
|---------------------|-------------------------|----------------|---------------|
| ITEM                | SPECIFICATION           | DETAILS        |               |
| GENERAL PERFORMANCE | Power Consumption       | 9W             | 14W           |
|                     | Lumens Delivered        | 800            | 1,500         |
|                     | Efficacy (lm/w)         | 89             | 107           |
|                     | CRI                     | ≥80            |               |
|                     | Color Temperature (CCT) | 3000K          |               |
|                     | Lumen Maintenance (L70) | 11,000 Hours   |               |
|                     | Dimmable                | No             |               |
| ELECTRICAL          | Power Factor            | ≥0.80          |               |
|                     | Input Voltage           | 120V           |               |
| PHYSICAL            | Base Type               | E26            |               |
|                     | Operating Temperature   | -4°F - 104°F   |               |
| CERTIFICATION       | Environment             | Dry, Damp      |               |
|                     | Warranty                | 1 Year Limited |               |

Lighting layouts and spacing criteria available upon request

**ORDERING:**

| ORDER CODE | MODEL NUMBER  | INPUT WATTAGE | EQUIVALENT WATTAGE | DELIVERED LUMENS | EFFICACY (LM/W) | CRI | CCT (K) | DIMENSIONS (D" x MOL") |
|------------|---------------|---------------|--------------------|------------------|-----------------|-----|---------|------------------------|
| 102611     | E9A19NDV30RS  | 9             | 60W Inc.           | 800              | 94              | 80  | 3000K   | 2.36" x 4.76"          |
| 102406     | E14A19NDV30RS | 14            | 100W Inc.          | 1,500            | 107             | 80  | 3000K   | 2.36" x 4.76"          |

Specifications are subject to change without notice.