

PROJECT NAME: \_\_\_\_\_ CAT. #: \_\_\_\_\_  
 NOTES: \_\_\_\_\_ FIXTURE SCHEDULE: \_\_\_\_\_

## Field Installable Outdoor Battery Backup Accessory



### Product Description:

The Field Installable Outdoor Battery Backup Accessory offers a life safety solution for many outdoor fixtures where there is a fixture size limitation, no battery backup option available or if it was forgotten. It covers 120-277V and can operate down to -20°C/-4°F. Consult the compatibility chart to see which fixtures it works with.

### Features:

- Covers 10-100W fixtures - see compatibility chart
- Test Switch and LED Indicator Light with self-diagnostic function
- NiCad Battery

### Installation:

- Direct Wall Mount
- Flex conduit connects to 1/2" threaded fixture hub

### Construction:

- Rugged die cast aluminum with corrosion resistant polyester powder coat finish
- Water tight flex conduit

### Listings:

- UL 924
- IP65

### Specifications

#### EM2-REMOTE-MT

Specifications	EM2-REMOTE-MT
Max Recharge Power Consumption	8W
Discharge Wattage	10W
Voltage	120-277V
Lumens	900-1,200lms (varies by fixture design)
Mounting	Wall with 12" flex conduit and 6" extended leads <b>(Hardware not included)</b>
Operating Temperature	-4°F-104°F (-20°C-40°C)
Weight	4.19 lbs
Listings	UL924, FCC, IP65

### Stocked Item

ORDER CODE	MODEL NUMBER	QTY PER CARTON
111294	EM2-REMOTE-MT	4

[Instruction Manual](#)

### LED Indicator Self-Diagnostic Codes

STATUS	STATUS	EXPLANATION
Off	Battery Mode	Battery in discharge mode
Red Stable	Charging Mode/Fully Charged	AC Mode, functioning correctly
Flashing 2 times	Battery Error	Battery disconnected or fail 90 minute test due to insufficient capacity
Flashing 3 times	Charging Error	Check input connection and stability
Flashing 5 times	Temperature Error	Over Temperature
Continuous Flashing	Abnormal LED load	Check output connection and stability



**3-year standard warranty** (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))

# Field Installable Outdoor Battery Backup Accessory

## Fixture Compatibility Chart

CANOPY/PARKING (CP & CPL)	WALLMAX CUTOFF (WPC & WTC)	WALLMAX OPEN FACE (WCF & WPOP)	M SERIES - REQUIRES W OR V MOUNT  <u>NOT WITH TWIST LOCK PHOTOCELL</u>	GUARDMAX DLC VERSIONS ONLY (SECS)  <u>NOT WITH PHOTOCELL</u>
 <p><b>CP</b> <b>CPL</b></p>	 <p><b>WPC</b> <b>WTC</b></p>	 <p><b>WCF</b> <b>WPOP</b></p>	 <p><b>Wall Mount</b> <b>Variable Wall Mount</b></p>	 <p><b>SECS15D</b> <b>SECS30</b></p>
CP20W	WPC15W	WCF29W	M40	SECS15D
CP30W	WPC20W	WCF40W	M55	SECS30
CP45W	WPC28W	WCF60W	M75	
CP55W	WPC40W	WCF80W	M100	
CP70W	WPC70W	WCF120W		
CPL20W	WPC100W	WPOP28W		
CPL30W	WTC15W	WPOP40W		
CPL40W	WTC25W	WPOP55W		
CPL52W	WTC29W	WPOP80W		
CPL60W	WTC50W			
	WTC75W			
	WTC120W			

## Dimensions

