



PROJECT NAME: _____
 NOTES: _____

CAT. #: _____
 FIXTURE SCHEDULE: _____

Fire Rated Slim Baffle Downlight

TRIAC - Color Selectable Series



Description:

The new Fire Rated Slim Baffle Downlight mounts directly into the ceiling, requiring no can. With a simple flick of a switch on the remote driver junction box, installers can choose from 2700K, 3000K, 3500K, 4000K or 5000K as CCT to suit various application needs. Low profile and easy to install, the Flush style fixture is Energy Star, Wet locations, IC rated and supports Title 24. Its edge lit optics providing an even, low glare illumination with an outstanding color rendering and Triac dimmability at 120v makes this the ideal choice for hospitality, retail, offices and multi-unit residential spaces.

Features:

- CCT Selectable: 2700K/ 3000K/3500K/4000K/5000K
- CRI: ≥90
- Beam angle: 110°
- Universal mounting plate available
- Mounts into ceiling without the use of a separate housing
- Field installable Emergency Battery back up kit available (includes a test switch and the charge indicator kit, no cover)
- Tested to UL 263 standards for 2-hour fire resistance

Dimming:

- TRIAC dimming (100%-10%) - 120V

Construction:

- Die cast Aluminum housing
- Plastic Lens

Listings:

- ULus (1598)
- UL263 Standard for fire rating
- UL Listed for wet locations
- ENERGY STAR certified
- IC rated
- Airtight construction
- Supports T24 Part 6 high efficacy lighting requirements

Ordering Information

FAMILY	SIZE	VOLTAGE/ DIMMING	WATTAGE (NOMINAL)	COLOR SELECTABLE	FINISH	SOURCING STRATEGY
FSDL= Fire Rated Slim Downlight Baffle Round	4= 4"	T= 120V only, TRIAC dimming	11= 11W	CS= 2700/3000/3500/4000/5000K (Default is 4000K)	W= White	TA= TAA Compliant
	6= 6"		15= 15W			
	8= 8"		19= 19W			

Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR #
111857	FSDL4T11CSWTA	3629766
111858	FSDL6T15CSWTA	3629767
111859	FSDL8T19CSWTA	3629768



5-year standard warranty (further details available at www.maxlite.com/warranties)



Fire Rated Slim Baffle Downlight *TRIAC - Color Selectable Series*

Dimming Compatibility

DIMMER BRAND	SERIES	DIMMER MODEL	DIMMER BRAND	SERIES	DIMMER MODEL
LEGRAND	Radiant	RHCL453PTC	LUTRON	Maestro C-L	MACL-153M
LEGRAND	Harmony	DCL453PTCCCV6	LUTRON	Skylark C-L	SCL-153P
LEGRAND	Harmony	HCL453PTCCCV6	LUTRON	Diva C-L	DVCL-153P
LEVITON	Sureslide	Cat.NO.6674	LUTRON	Skylark	CTCL-153PDH-WH
LEVITON	Illumena Tech	R50-IPL06-10M	LUTRON	Diva C-L	DVWCL-153PH-WH

Accessories (Sold Separately)

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
112240	SD-UNVTEMPLATE-2	SLIM DOWNLIGHTS, ROUGH IN TEMPLATE, UNIVERSAL 4", 6", 8"	
100298	EBUUP15007N0100	EMERGENCY BATTERY BACK UP, 07W, 100-347V, FIELD INSTALLABLE	
108566	EBUUP17015N200B	EMERGENCY BATTERY BACK UP, 15W, 120-347VAC, CEC COMPLIANT, FIELD INSTALLABLE	
112239	SDL-EXTCBL6-W	EXTENSION CABLE, 6FT, WHITE	
14099684	RR-XRING6	6" EXTRA WIDE TRIM RING (Compatible only with FSDL6T15CSW)	
14099685	RR-XRING8	8" EXTRA WIDE TRIM RING (Compatible only with FSDL8T19CSW)	
110875	TRC-600W-010V	TRIAC CONVERTER 0-10V WITH 12V AUX TRC-600W-010V Data Sheet	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> Scan QR Code to view the data sheet </div>

c-Max Network
****Requires TRC-600W-010V installed to fixture**

105895	NN-MGT	NETWORK NODE MAGNET, TRANSLUCENT	
109111	WNS3-W	3 BUTTON WALL NETWORK SWITCH (BLUETOOTH) WHITE	
108392	WNS5-W	5 BUTTON WALL NETWORK SWITCH (BLUETOOTH) WHITE	
106318	NPP-300W	120-277V NETWORK POWER PACK 300W MAX	
107788	NPPSL-PSW	NETWORK POWER PACK PIR SENSOR, 12V, WHITE	



Fire Rated Slim Baffle Downlight

TRIAC - Color Selectable Series

Specifications

	FSDL4T11CSWTA	FSDL6T15CSWTA	FSDL8T19CSWTA
Power Consumption	11W	15W	19W
Equivalency	75W INC	75W INC	125W INC
Lumens Delivered	900 lm	1250 lm	1600 lm
Lumens Battery Mode EBUUP15007N0100	800 lm	900 lm	1,100 lm
Lumens Battery Mode EBUUP17015N200B	800 lm	900 lm	1,100 lm
Efficacy	82 lm/w	83 lm/w	84 lm/w
Beam Angle	110°		
CRI	≥90		
Color Temperature (K)	2700K/3000K/3500K/4000K/5000K (Default is 4000K)		
L70 Lumen maintenance	≥ 50,000Hrs		
Power Factor	≥ 0.9		
Input Voltage	120V, 60Hz		
Dimming	Triac Dimming Range: 10%-100%		
THD	<20% @ 120V		
Operating Temperature	-4°F to 104°F (-20°C to 40°C)		
Listings	ULus (1598), FCC, Title 24 Compliant, JA8, IC Rated, Airtight, UL263 standard for 2-hour fire resistance		
Environment	UL listed for Wet location		
Warranty	5 Year Warranty		

Fire Rated Slim Baffle Downlight *TRIAC - Color Selectable Series*

Dimensions:

