

**VANITY BAR**  
ML8 SERIES - BULB IN BOX



**PRODUCT DESCRIPTION:**

LED Vanity Bar provides long-lasting, even illumination for both residential and commercial property applications. Available in 2ft, the Vanity Bar is constructed with a high transmission glass diffuser and is available in nickel, white, or dark bronze finish. This bulb in a box solution comes prepackaged with JA8 compliant E26 based LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

**FEATURES:**

- CRI: ≥90
- JA8 compliant flicker free bulb included (E26 Base)
- Dedicated Voltage: 120V, 60Hz
- Five year limited warranty
- Triac dimming standard
- Operating Temperature: 0°F to 104°F

**CONSTRUCTIONS: WARRANTY:**

- Formed steel
  - Powder coat finish
  - Glass Tulip Shade
- 5-year standard warranty\* (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))  
\*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

**ORDERING:**

| FAMILY           | TYPE                             | OUTPUT                   | STYLE     | FINISH                  | CCT/CRI           | CAPABILITIES            |
|------------------|----------------------------------|--------------------------|-----------|-------------------------|-------------------|-------------------------|
| ML8= Vanity Bars | E= Edison Base E26 Bulb included | 303= 3 x 10W Lamps, 120V | TU= Tulip | WH= White<br>NI= Nickel | 27= 2700K, 90 CRI | -V2= JA8 Compliant Bulb |

**SPECIFICATIONS:**

| ITEM                | SPECIFICATION          | 1408625                          | 1408626       |
|---------------------|------------------------|----------------------------------|---------------|
|                     |                        | ML8E303TUNI27                    | ML8E303TUWH27 |
| GENERAL PERFORMANCE | Power Consumption (W)  | 30 (3 x 10)                      | 30 (3 x 10)   |
|                     | Source Lumens          | 2,400                            | 2,400         |
|                     | Efficacy (lm/W)        | 80                               | 80            |
|                     | Color Temperature (K)  | 2700K                            |               |
|                     | CRI                    | ≥90                              |               |
|                     | L70 Lumen Maintenance  | 25,000 hours                     |               |
| ELECTRICAL          | Input Voltage          | 120V                             |               |
|                     | Input Frequency        | 60Hz                             |               |
|                     | Power Factor           | ≥0.9                             |               |
| PHYSICAL            | Dimensions (L x W x H) | 23" x 10" x 9"                   |               |
|                     | Finish                 | Brushed Nickel, White, or Bronze |               |
|                     | Operating Temperature  | 0°F to 104°F                     |               |
| CERTIFICATION       | Environment            | Suitable for Damp Locations      |               |
|                     | Certification          | Energy Star, cETLus, FCC         |               |
|                     | Warranty               | 5-year standard warranty*        |               |