

**ROUND PENDANT**  
MLRP G2 SERIES



**INDIRECT**

**PRODUCT DESCRIPTION:**

The LED Round Pendant is a high performance fixture with an appearance that will enhance any office, home, school, hospital or hospitality space. The edge lit design of the LED Round Pendant produces an even, consistent shadowless light. The pendants are fully dimmable using the 0-10V protocol and are compatible with building controls, motion sensors, timers, and other systems using the same protocol. The quality constructed LED panel will provide beautiful light for years!

**FEATURES:**

- Integral driver
- Universal Voltage: 120-277V
- 0-10V dimming standard
- 10 year warranty
- CRI >80
- Can be suspension mounted
- Suitable for damp locations
- Light distribution 70%/30%
- 6 foot suspension cables included

**WARRANTY:**

10-year standard warranty with labor allowance\* (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))  
\*Warranty Limitations: Product must be rated for the application per the Product Data Sheet (PDS); operated ≤ 16 hrs; in ambient of -29F to 104F.  
\*Up to \$25/unit; labor allowances of up to \$500/unit available for purchase – contact MaxLite representative for details.



| MODEL SELECTION     |         |             | Typical order example: MLRP24E4035I |                        |               |
|---------------------|---------|-------------|-------------------------------------|------------------------|---------------|
| FAMILY              | SIZE    | EDGE LIT    | WATTAGE                             | CCT                    | TYPE OF LIGHT |
| MLRP= Round Pendant | 24= 24" | E= Edge Lit | 40= 40W                             | 35= 3500K<br>40= 4000K | I = Indirect  |

**SPECIFICATIONS:**

MLRP24E40XXI

| ITEM                       | SPECIFICATION         | DETAILS                               |
|----------------------------|-----------------------|---------------------------------------|
| <b>GENERAL PERFORMANCE</b> | Power Consumption (W) | 36W                                   |
|                            | Lumens Delivered (lm) | 3,200                                 |
|                            | Efficacy (lm/W)       | 89                                    |
|                            | CRI                   | ≥80                                   |
|                            | Color Temperature (K) | 3500, 4000                            |
|                            | L70 Lifetime (hours)  | 50,000                                |
|                            | Color Consistency     | Proprietary binning for uniform color |
| <b>ELECTRICAL</b>          | Power Factor          | ≥0.9                                  |
|                            | Input Voltage         | 120-277V                              |
|                            | Compatible Dimmers    | 0-10V Dimming                         |
| <b>PHYSICAL</b>            | Weight                | 4.5 lbs                               |
|                            | Mounting              | Suspension                            |
|                            | Operating Temperature | -4°F to 104°F                         |
|                            | Humidity              | 10-80% RH, non-condensing             |
| <b>QUALIFICATION</b>       | Qualification         | FCC, cETLus                           |
|                            | Material Usage        | RoHS compliant; no mercury            |
|                            | Environment           | Damp                                  |
|                            | Warranty              | 10 year warranty*                     |

**ORDERING TABLE:**

| ORDER CODE | MODEL NUMBER | WATTAGE | CCT   | TYPE OF LIGHT | MOUNTING   |
|------------|--------------|---------|-------|---------------|------------|
| 1410240    | MLRP24E4035I | 40W     | 3500K | INDIRECT      | SUSPENSION |
| 14099709   | MLRP24E4040I | 40W     | 4000K |               |            |

**DIMENSIONS:**

