

SECURITY FIXTURE CYLINDER AND GLOBE - LAMP INCLUDED



CYLINDER



GLOBE

PRODUCT DESCRIPTION:

The Cylinder and Globe Security Lights provide efficient entryway lighting for commercial, light commercial and multi-unit residential applications. The wall mount version is equipped with a dusk-to-dawn photocell and cap for further energy savings. Both models include a JA8 listed LED bulb that supports Title 24 requirements in California.



DIMMING:

- 120V option available with 120V triac dimming (10%)

MOUNTING:

- Ceiling and wall mount options

CONTROLS:

- Dusk to dawn photocell available on the wall mount option
Photocell can be disabled by covering with a cover cap (included standard in the fixture)

CONSTRUCTION:

- Die cast Aluminum housing
- Plastic cylinder lens
- Plastic and glass globe lens

LISTINGS:

- ETL listed for Wet Locations, Outdoor
- ENERGY STAR Certified
- Supports T24 Part 6 high efficacy lighting requirements

WARRANTY:

5-year standard warranty (further details available at www.maxlite.com/warranties) Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

ORDERING STRUCTURE

FAMILY	SUBFAMILY	BASE	MOUNTING OPTIONS	WATTAGE (NOMINAL)	FINISH	CONTROLS
SEC= Security fixtures	C= Cylinder style	E= Edison Base, E26	W'= Wall mount C= Ceiling Mount	9= 09W	B= Bronze W²= White L²= Black	PC¹= Photocell with cover cap

¹Photocell option is only available with wall mount Photocell

²Contact MaxLite for lead times


ORDER CODE

ORDER CODE	MODEL NUMBER	ES PRODUCT ID
103898	SECCEW09BPC	13023841
103899	SECCEC09B	13023841

COMPATIBLE DIMMERS

DIMMER BRAND	MODELS
LEVITON	6631, 6672, 6683, 603-6631-A, 6631-A, 6683-10Z, IPI06-1LZ, IPI10-1LZ, IPL0
LUTRON	AYCL-153P-WH, AYCL-153PH, DVCL-153P-WH, DVWCL-153PH-WHC, S-603PH-WH, SCL-153PH-WH, TGCL-153PH-WH

ACCESSORIES (SOLD SEPARATELY)

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
104755	SECGG	LENS, SECURITY SECC SERIES, GLOBE STYLE, GLASS	
104756	SECGP	LENS, SECURITY SECC SERIES, GLOBE STYLE, PLASTIC	

SPECIFICATIONS

	SECCEC09B	SECCEW09B
	DETAILS	
Nominal Wattage (W)	9	
Lumens Delivered (lm)	800	
Equivalency	60W INC	
Efficacy (lm/W)	88	
Beam Angle	225°	
CRI	≥90	
Color Temperature (K)	3000K	
L70 Lifetime (Hrs)	≥25,000 Hrs	
Voltage	120V, Triac Dimming, 10%	
Power Factor	≥0.90	
Housing	Die Cast Aluminum	
Lens	Plastic Cylinder lens	
Mounting	Ceiling and wall mount	
Operating Temperature	-4°F to 104°F	
Listings	ENERGY STAR, Title 24, cETLus, FCC	
Environment	Wet locations, Indoor	
Warranty	5 years	

PRODUCT DIMENSIONS:

