



PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

TRK Troffer Retrofit Kit Control Ready Series Wattage and Color Select



Product Description:

MaxLite's innovative Troffer Retrofit Kit offers an economical solution to upgrade existing fixtures to LED technology. The Troffer Retrofit kit can be retrofitted into most existing troffers in under 15 minutes. Optional trim plates can be included and are a great way to give a "clean" look to the installed fixture. With a Wattage and CCT select option, each unit provides up to 9 variations of the product giving flexibility to the end users and distributors.

Features:

- Power/Wattage selectable
- Controls Ready – can be paired with the new cMax controls nodes
- Quick installation of Troffer Retrofit Kit in existing luminaire without the need to break the ceiling plenum
- CCT Selectable: 3500K/4000K/5000K for 20W & 25W models
- On EM mode, The fixture CCT will be set to 5000K
- On EM mode, the fixture output a minimum of 700 lumens for 90 minutes, when fully charged
- Dimming: 0-10V with 5-100% Dimming Range with Dim-to-off capability

Controls Ready:

MaxLite's new Controls Ready (CR) fixtures allows for quick and easy in-field installation (plug and play) of controls. Simply purchase any CR fixture and the required Controls Node and you're all set! See the accessory table for all controls options available for this fixture.



Ordering Structure

| FAMILY | SIZE | DIMMABLE | WATTAGE SELECTABLE | COLOR TEMPERATURE | CONTROLS | OPTIONS |
|-------------------------------|-----------|-------------|--------------------|--|-------------------|--|
| TRK= LED Troffer Retrofit Kit | 14= 1'x4' | D= Dimmable | 20W= 20W, 25W, 30W | CS= Color Selectable (3500K, 4000K, 5000K) | CR= Control Ready | [BLANK]= None EM= Emergency Battery Backup Unit |
| | 22= 2x2' | | 20W= 20W, 25W, 30W | | | |
| | 24= 2'x4' | | 25W= 25W, 30W, 34W | | | |
| | SIZE | | WATTAGE | | | |
| 22= 2'x2' | 18= 18W | 40= 4000K | | | | |
| 24= 2'x4' | 28= 28W | 40= 4000K | | | | |

Only 2x2 18W and 2x4 28W are available in 4000K
 Default setting for WCS models is set to lowest wattage and 4000K.

Stocked Items

| ORDER CODES | MODEL NUMBER | DLC PRODUCT ID | ORDER CODES | MODEL NUMBER | DLC PRODUCT ID |
|-------------|---------------|----------------|-------------|--------------|----------------|
| 104319 | TRK14D20WCSCR | P3NOX8IH | 105576 | TRK22D1840CR | P277E2AW |
| 105571 | TRK22D20WCSCR | P9UOKXHA | 105578 | TRK24D2840CR | PJT74GXC |
| 105573 | TRK24D25WCSCR | P86A5YZE | | | |



10-year standard warranty with labor allowance (further details available at www.maxlite.com/warranties)

Warranty Limitations: Product must be rated for application per the Product Data Sheet (PDS); operated ≤16 hrs; in ambient temperatures -4°F to 77°F. If ambient temperatures fall outside the -4°F to 77°F range, product is warranted for 5 years according to the operating temperature range specified on the PDS. Up to \$25/unit; registration required. Additional coverage may be available for purchase; contact MaxLite. Excludes EM/MS versions; component warranty applies.



TRK Troffer Retrofit Kit Control Ready Series

Wattage and Color Select

Accessories (SOLD SEPARATELY)

| ORDER CODE | MODEL NUMBER | DESCRIPTION | IMAGE |
|--------------------|--------------|--|-------|
| 109790 | TRK-ARB-24 | Troffer Retrofit Kit Air Return Bracket 24 Inches - For Use With 2x2 TRK | |
| 109789 | TRK-ARB-48 | Troffer Retrofit Kit Air Return Bracket 48 Inches - For Use With 2x4 And 1x4 TRK | |
| c-Max Basic | | | |
| 105567 | CN-REMOTE | Control Node Remote Control | |
| 105564 | CN-RTMST | Control Node Rectangular, Microwave Motion Sensor, Translucent | |
| 105890 | CN-RTPSW | Control Node Rectangular, PIR Motion Sensor/Daylight Harvesting, White | |

*Maxlite recommends CN-RTPSW (PIR) sensor for most applications with this fixture.
If CN-RTMST(microwave) is required for an application, Maxlite recommends a pilot test to confirm there is no interference that causes unexpected responses from the microwave sensor.

| c-Max Network | | | |
|----------------------|----------|--|--|
| 105892 | NN-RTW | Network Node Rectangular, White | |
| 105893 | NN-RTDHW | Network Node Rectangular, Daylight Harvesting, White | |
| 106059 | NN-RTPSW | Network Node Rectangular, PIR Motion Sensor/Daylight Harvesting, White | |
| 108392 | WNS5-W | 5 Button Wall Network Switch (Bluetooth) White | |
| 106318 | NPP-300W | 120-277V Network Power Pack 300W Max | |

Sensor

| SENSOR | TECHNOLOGY | DIMMING | DAYLIGHT HARVESTING | REMOTE CONTROL | QR CODE |
|----------|--|----------|----------------------------------|-------------------------------|---------|
| CN-RTMST | Microwave, Photoelectric | Bi-Level | N/A | Yes | |
| CN-RTPSW | PIR, Photoelectric | Bi-Level | Continuous Adjustment Mode (CAM) | Yes | |
| NN-RTW | Bluetooth networking | N/A | N/A | c-Max App (iPhone or Android) | |
| NN-RTDHW | Photoelectric & Bluetooth networking | N/A | Continuous Adjustment Mode (CAM) | c-Max App (iPhone or Android) | |
| NN-RTPSW | PIR motion sensing, Photoelectric & Bluetooth networking | Bi-Level | Continuous Adjustment Mode (CAM) | c-Max App (iPhone or Android) | |



TRK Troffer Retrofit Kit Control Ready Series

Wattage and Color Select

Specifications

| | | TRK14D20WCSCR | | |
|-----------------------|-------------------------------|-------------------|-----|-------------------|
| Size | 1X4 | | | |
| Power Consumption | 20W | 25W | 30W | |
| Lumens Delivered | 2620/2640/2660 lm | 3250/3225/3200 lm | | 3810/3780/3750 lm |
| Efficacy | 133/132/131 lm/w | 130/129/128 lm/w | | 127/126/125 lm/w |
| CRI | ≥80 | | | |
| Color Temperature (K) | 3500K, 4000K, 5000K | | | |
| L70 Lumen maintenance | ≥100,000 Hrs | | | |
| Input Voltage | 120-277V, 50/60 Hz | | | |
| Power Factor | >0.9 | | | |
| Surge Protection | 2.5KV | | | |
| Operating Temperature | -4°F TO 122°F (-20°C TO 50°C) | | | |
| Humidity | 10% to 80% RH non-condensing | | | |
| Certification | FCC, cULus Classified | | | |
| Material Usage | RoHS Compliant; No Mercury | | | |
| Environment | Damp/Dry Location | | | |
| Qualifications | DLC Premium | | | |

See page 1 footer

Specifications

| | | TRK22D20WCSCR | | | TRK22D1840CR |
|-----------------------|-------------------------------|-------------------|-------------------|----------|--------------|
| Size | 2X2 | | | | |
| Power Consumption | 20W | 25W | 30W | 18W | |
| Lumens Delivered | 2660/2640/2620 lm | 3250/3225/3200 lm | 3810/3780/3750 lm | 2471 lm | |
| Efficacy | 133/132/131 lm/w | 130/129/128 lm/w | 127/126/125 lm/w | 128 lm/w | |
| CRI | ≥80 | | | | |
| Color Temperature (K) | 3500K, 4000K, 5000K | | | | 4000K |
| L70 Lumen maintenance | ≥100,000 Hrs | | | | |
| Power Factor | 120-277V, 50/60 Hz | | | | |
| Surge Protection | 2.5KV | | | | |
| Input Voltage | >0.9 | | | | |
| Operating Temperature | -4°F TO 122°F (-20°C TO 50°C) | | | | |
| Humidity | 10% to 80% RH non-condensing | | | | |
| Certification | FCC, cULus Classified | | | | |
| Material Usage | RoHS Compliant; No Mercury | | | | |
| Environment | Damp/Dry Location | | | | |
| Qualifications | DLC Premium | | | | |

See page 1 footer

MaxLite**eMax**
CONTROLS COMPATIBLE

TRK Troffer Retrofit Kit Control Ready Series

Wattage and Color Select

Specifications

| Specifications | TRK24D25WCSCR | | | TRK24D2840CR |
|-----------------------|-------------------------------|-------------------|-------------------|--------------|
| | 25W | 30W | 35W | 28W |
| Size | 2X4 | | | |
| Power Consumption | 25W | 30W | 35W | 28W |
| Lumens Delivered | 3325/3300/3275 lm | 3900/3870/3840 lm | 4318/4284/4250 lm | 3510 lm |
| Efficacy | 133/132/131 lm/w | 130/129/128 lm/w | 127/126/125 lm/w | 126 lm/w |
| CRI | ≥80 | | | |
| Color Temperature (K) | 3500K, 4000K, 5000K | | | 4000K |
| L70 Lumen maintenance | ≥100,000 Hrs | | | |
| Power Factor | 120-277V, 50/60 Hz | | | |
| Surge Protection | 2.5KV | | | |
| Input Voltage | >0.9 | | | |
| Operating Temperature | -4°F TO 122°F (-20°C TO 50°C) | | | |
| Humidity | 10% to 80% RH non-condensing | | | |
| Certification | FCC, cULus Classified | | | |
| Material Usage | RoHS Compliant; No Mercury | | | |
| Environment | Damp/Dry Location | | | |
| Qualifications | DLC Premium | | | |

See page 1 footer

TRK Troffer Retrofit Kit Control Ready Series *Wattage and Color Select*

Dimensions

