


WALL SCONCE
ML9 SERIES - LED INTEGRATED



ORDERING:

ORDER CODE	MODEL NUMBER	ITEM DESCRIPTION
1408702	ML9LARBN23827	WALL SCONCE LED 10.5" ARCHITECTURAL BRUSHED NICKEL 23W 80CRI 2700K
1409631	ML9LARBN23830	WALL SCONCE LED 10.5" ARCHITECTURAL BRUSHED NICKEL 23W 80CRI 3000K
14098778	ML9LARBN23840	WALL SCONCE LED 10.5" ARCHITECTURAL BRUSHED NICKEL 23W 80CRI 4000K

SPECIFICATIONS:

ML9LARBN23827

ITEM	SPECIFICATION	
GENERAL PERFORMANCE	Power Consumption (W)	23
	Delivered Lumens	1,891
	Efficacy (lm/W)	83
	Color Temperature (K)	2700K (Additional CCT available, contact MaxLite for info.)
	CRI	≥80
	L70 Lumen Maintenance	50,000 hours
ELECTRICAL	Input Voltage	120V
	Input Frequency	60Hz
	Power Factor	≥0.9
PHYSICAL	Dimensions (L x W x H)	10.5"L x 9.4"W x 3.9"H
	Finish	Brushed Nickel
	Operating Temperature	-4°F to 104°F (-20°C - 40°C)
CERTIFICATION	Environment	Suitable for Damp Locations
	Certification	Energy Star, ETL, FCC
	Warranty	5 year limited warranty

PRODUCT DESCRIPTION:

The LED Wall Sconce provides long-lasting illumination with a decorative touch to corridors in hotels, motels and commercial property applications. This LED integrated Wall Sconce offers higher efficiency and longer lifetime than fluorescent equivalents, leading to increased energy savings and reducing the amount of maintenance required.

FEATURES:

- CRI ≥80 and flicker free
- Triac dimming
- Dedicated voltage: 120V
- Suitable for damp locations
- 5 year warranty

CONSTRUCTIONS:

- Die formed steel
- Powder coat
- High transmission lens

COMPATIBLE DIMMERS :

LUTRON	DVCL-153P
LUTRON	LGCL-153PLH
LUTRON	DVLV-600PH
LUTRON	CTCL-153P
LUTRON	6672