

LED VOLUMETRIC PANEL

Designed as cost-effective replacements for traditional fluorescent troffers, the DesignLights Consortium®-qualified Volumetric LED Panels are ideal for installation in T-bar grid or drop-in ceilings. Excellent color rendering and smooth light output from ceiling to floor.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(L"XW"XH")	EQUIV.
LED VOLUMETRIC PANEL - 2X2								
436R34	36	3,784	109	120-277	80	3500K	23.74"x23.74" x3.54"	3 x 17W T8
53XH77	36	3,954	113	120-277	80	4000K	23.74"x23.74" x3.54"	3 x 17W T8
LED VOLUMETRIC PANEL - 2X4								
53DK20	45	5,343	133	120-277	80	4000K	47.20"x23.74" x3.54"	3 x 32W T8
53XH78	45	5,142	125	120-277	80	3500K	47.20"x23.74" x3.54"	3 x 32W T8



LED EDGE LIT FLAT PANELS

Designed for drop in ceilings, Edge Lit LED Flat Panels are the ideal energy-efficient replacements for fluorescent fixtures in offices, schools, hospitality, healthcare and other commercial and industrial applications that require slim installation depth.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED EDGE LIT FLAT PANEL 2X2								
53XH70	30	3,000	100	120-277	80	3500K	23.74"x23.74" x1.7"	3 x 17W T8
53DK24	30	3,000	100	120-277	80	4100K	23.74"x23.74" x1.7"	3 x 17W T8
53XH71	36	4,460	127	120-277	80	3500K	23.74"x23.74" x1.7"	4 x 17W T8
53XH72	36	4,550	127	120-277	80	4100K	23.74"x23.74" x1.7"	4 x 17W T8
LED EDGE LIT FLAT PANEL 2X4								
53XH73	37	4,000	100	120-277	80	3500K	47.72"x23.74" x1.7"	3 x 32W T8
53XH74	37	4,000	100	120-277	80	4100K	47.72"x23.74" x1.7"	3 x 32W T8
53XH75	48	5,700	129	120-277	80	3500K	47.72"x23.74" x1.7"	4 x 32W T8
53XH76	48	5,810	130	120-277	80	4100K	47.72"x23.74" x1.7"	4 x 32W T8



LED RECESSED TROFFER

Designed with the look of a traditional fluorescent fixture, the ECO-T™ LED Recessed Troffer offers a classic recessed troffer housing with LED strips that emulate fluorescent lamps, but operates with the energy saving and long life benefits of LED technology.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
2X2 - LED RECESSED TROFFER								
39UR99	32	3,440	100	120-277	80	4000K	23.70"x23.70" x3"	3 x 17W T8
2X4 - LED RECESSED TROFFER								
53DK25	42	4,520	107	120-277	80	4000K	10.50"x9.72" x4.6"	3 x 32W T8



LED LENSED RETROFIT KIT

The LED Lensed Retrofit Kit (LRK) installs into existing troffers without the need to enter the ceiling space, giving facility managers the quickest, most cost effective means of replacing outdated fluorescent lighting systems with the high efficiency and performance of LEDs.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
2X2 - LED LENSED RETROFIT KIT								
53DK22	30	2,740	99	120-277	80	4100K	21.4"x21.4" x2.70"	3 x 17W T8
53XH79	30	2,640	98	120-277	80	3500K	21.4"x21.4" x2.70"	3 x 17W T8
2X4 - LED LENSED RETROFIT KIT								
53XH80	40	4,060	112	120-277	80	3500K	45.43"x22.54" x2.82"	3 x 32W T8
53XH81	40	4,130	113	120-277	80	4100K	45.43"x22.54" x2.82"	3 x 32W T8



LED RECESSED RETROFIT DOWNLIGHT

Designed as an energy-efficient lighting solution for remodeling or new construction projects, LED Recessed Retrofit downlights are the ideal replacements for 50- to 75-watt incandescent lamps in the industry's most popular four- and six-inch recessed downlight fixtures.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
4" LED RECESSED RETROFIT DOWNLIGHT								
49WJ32	10	712	75	120	80	2700K	5.35"x5.35" x3.43"	60w Inc.
53FN79	10	712	75	120	80	3000K	5.35"x5.35" x3.43"	60w Inc.
6" LED RECESSED RETROFIT DOWNLIGHT								
49WJ33	11	880	80	120	80	2700K	7.48"x7.48" x3.60"	75W Inc.
53FN80	11	900	82	120	80	3000K	7.48"x7.48" x3.60"	75W Inc.



LED ROUND PENDANT HIGH BAY

LED Round Pendant High Bays are designed for 25-foot and higher ceiling applications in warehouses, manufacturing plants, large retail centers, gymnasiums, houses of worship and other facilities that require significant mounting heights.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED ROUND PENDANT HIGH BAY								
53DK17	85	11,900	140	120-277	82	5000K	11.75"x10.30" x12.10"	200W MHL



LED LINEAR HIGH BAY

The LED Linear Highbay offers leading-edge efficacy and scalability for high ceiling applications such as warehouses, distribution centers, manufacturing facilities and big box retailers.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED LINEAR HIGH BAY								
53DK18	100	13,487	129	120-277	78	5000K	24.06"x13.69" x2.73"	4 x 54W T5HO



LED ECONOMICAL HIGH BAY

The Economic High Bay Series is a cost-effective and quality solution for lighting warehouses, distribution centers, manufacturing facilities, big box retailers, and other industrial applications.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED ECONOMICAL HIGH BAY								
452N11	133	17,400	130	120-277	80	5000K	23.80"x17.3" x3.62"	6 x 54W T5 HO
452N12	162	20,700	130	120-277	80	5000K	23.80"x17.3" x3.62"	400W HID



LED VAPOR TIGHT FIXTURE

A cost effective LED Vapor Tight Fixture, features full length polycarbonate lens, one piece white (PC) Polycarbonate body. Designed to meet or exceed IES recommended Fc at installed heights for parking drive lane compliance. For uses as utility lighting, parking garage, stairwell lighting, and low bay lighting where meets applicable building and safety codes.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(L"XW"XH")	EQUIV.
2-FT LED VAPOR TIGHT								
436R27	20	2,966	134	120-277	86	4000K	26"x6.75"x4.75"	2 x 17W T8
436R28	20	2,850	131	120-277	80	5000K	26"x6.75"x4.75"	2 x 17W T8
4-FT LED VAPOR TIGHT								
436R29	20	2,912	138	120-277	87	4000K	50"x6.75"x4.75"	2 x 32W T8
436R30	20	2,977	140	120-277	86	5000K	50"x6.75"x4.75"	2 x 32W T8
436R31	30	4,377	133	120-277	87	4000K	50"x6.75"x4.75"	3 x 32W T8
436R32	30	4,360	134	120-277	80	5000K	50"x6.75"x4.75"	3 x 32W T8
4-FT LED VAPOR TIGHT ECONOMY								
53DK26	40	4,244	117	120-277	80	4000K	50"x6.75"x4.75"	2 x 32W T8



LED UTILITY WRAPS

The DesignLights Consortium-qualified LED Utility Wraps Series is a cost-effective, energy-efficient lighting solution that meets building and safety codes for high-occupancy dwellings, parking garages, stairwells and other commercial utility applications.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
4-FT LED UTILITY WRAP								
39UU85	20	2,794	130	120-277	86	4000K	48.75"x6.75" x2.50"	2x32W T8
4-FT LED UTILITY WRAP ECONOMY								
53DK27	40	4,341	106	120-277	80	4000K	48.7"x6.5" x2.54"	3 x 32W T8



LED LOW PROFILE CANOPY

Quick to install and pay for itself, the LED Low-Profile Canopy is an economical retrofit solution for 150-250W HID garage and canopy luminaires.



SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
PLANETARY GEAR WINCHES								
446M66	20	2,248	116	120-277	70	5000K	10.23"x10.23" x3.44"	100W MH
446M67	30	3,321	111	120-277	76	5000K	10.23"x10.23" x3.44"	150W MH
53DK23	42	4,645	100	120-277	77	5000K	10.23"x10.23" x3.44"	175W MH
446M59	53	6,094	115	120-277	77	5000K	10.23"x10.23" x3.44"	250W MH

LED WALL PACKS

LED Wall Packs feature leading-edge optics that increase light output and reduce shadows to create safe, brightly-lit outdoor environments in parking garages and entrances, public areas, schools, hospitals, hotels and outdoor walkways nationwide.



SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED SMALL WALL PACKS								
452N13	26	2,777	109	120-277	84	5000K	7.48"x13.77" x8.66"	150W MH
446M62	40	3,985	99	120-277	84	5000K	7.48"x13.77" x8.66"	175W MH
446M63	46	4,801	104	120-277	84	5000K	7.48"x13.77" x8.66"	250W MH
LED LARGE WALL PACK								
54EP98	77	8,604	112	120-277	82	5000K	9.40"x17" x9"	400W MH
49WJ09	38	3,480	91	120-277V	84	5000K	9.40"x17" x9"	175W MH
49WJ10	53	4,776	90	120-277V	82	5000K	9.40"x17" x9"	250W MH

LED ADJUSTABLE WALL PACKS

LED Adjustable Wall Packs are constructed with pivoting heads that aim light precisely while minimizing glare and backlight. These durable, energy-saving fixtures are perfect for lighting outdoor walkways, landscapes, parking areas and perimeters.



SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED SMALL ADJUSTABLE WALL PACK								
54EP96A	15	1,690	105	120-277	70	4000K	7.44"x 6.22"x 3.7"	100W MH
54EP96	15	1,575	105	120-277	70	5000K	7.44"x 6.22"x 3.7"	100W MH
452N14A	20	2,110	105	120-277	70	4000K	7.44"x 6.22"x 3.7"	150W MH
452N14	20	2,100	105	120-277	70	5000K	7.44"x6.22"x3.7"	150W MH
446M64A	29	3,000	105	120-277	70	4000K	7.44"x6.22"x3.7"	175W MH
446M64	29	3,000	105	120-277	70	5000K	7.44"x6.22"x3.7"	175W MH
LED LARGE ADJUSTABLE WALL PACK								
446M65A	50	4,500	105	120-277	70	4000K	10.50"x9.72"x4.6"	250W MH
446M65	50	5,250	105	120-277	70	5000K	10.50"x9.72"x4.6"	250W MH
452N15A	70	7,790	116	120-277	70	4000K	10.50"x9.72"x4.6"	250W MH
452N15	70	8,200	116	120-277	70	5000K	10.50"x9.72"x4.6"	250W MH

LED SLIM AREA LIGHT

The LED Slim Area Lights delivers class-leading efficacy in a lightweight design that can be effortlessly applied to new and retrofit outdoor projects. Offered in lumen packages ranging from 7,700 lm to over 35,000 lm, this series achieves up to 129 lumens per watt while providing significant long-term energy and maintenance cost savings.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(L"XW"XH")	EQUIV.
LED SLIM AREA LIGHT W/ STRAIGHT ARM MOUNT								
436R33	60	7,994	133	120-277	75	5000K	22.48"x12.28" x3.22"	150W PSMH
446M57	100	12,541	125	120-277	75	5000K	22.48"x12.28" x3.22"	250W PSMH
LED SLIM AREA LIGHT W/ SLIPFITTER KNUCKLE MOUNT								
446M61	60	7,994	133	120-277	75	5000K	22.48"x12.28" x3.22"	150W PSMH
446M58	100	12,541	125	120-277	75	5000K	22.48"x12.28" x3.22"	250W PSMH



LED BULLET FLOODS

LED Bullet Flood Lights provide energy-efficient, directional lighting for landscape, facade and outdoor signage. Sealed to keep out dirt, bugs and moisture, the Bullet is constructed with a precision die-cast aluminum housing and tempered, shatter-resistant glass for durability.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED BULLE FLOODS								
39UU96	11	1,206	111	120-277	75	3000K	4.2"x4.2" x8.3"	50W QH
39UU97	11	1,235	114	120-277	75	5000K	4.2"x4.2" x8.3"	50W QH
39UU86	28	3,121	114	120-277	73	3000K	5.3"x5.3" x10"	150W MH
39UU89	28	3,184	116	120-277	76	5000K	5.3"x5.3" x10"	150W MH



LED SMALL FLOODS

Small LED Flood Lights create bright, shadow-free security and spot lighting for a variety of outdoor applications, including facades, landscapes, public places, retail and residential complexes, and hospitality.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED SMALL FLOODS								
49WJ22	13	1,261	95	120-277	75	5000K	3.46"x4.61" x5.15"	100W QH
49WJ23	19	1,981	109	120-277	75	5000K	21.4"x21.4" x2.70"	150W MH
49WJ24	36	4,010	112	120-277	75	5000K	21.4"x21.4" x2.70"	175W QH
453D94	49	5,227	107	120-277	75	5000K	21.4"x21.4" x2.70"	150W MH
LED SMALL FLOODS - NARROW								
49WJ16	13	1,255	96	120-277	75	5000K	45.43"x22.54" x2.82"	100W QH
49WJ17	19	2,002	111	120-277	75	5000K	45.43"x22.54" x2.82"	150W MH
49WJ18	35	3,709	105	120-277	75	5000K	45.43"x22.54" x2.82"	175W QH



LED ARCHITECTURAL SECURITY LIGHT

The Architectural Security Light with integrated dusk-to-dawn photocell combines performance and design. It provides years of maintenance free illumination for many outdoor residential, commercial and industrial applications with low mounting heights.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED ARCHITECTURAL SECURITY LIGHT								
49WJ15	53	6,122	116	120-277	82	5000K	9.4"x17.0" x9.0	175W MH



LED MEDIUM AREA LIGHT

LED Medium Area Lights are efficient, energy saving replacements for metal halide and high-pressure sodium fixtures, containing an universal voltage driver.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED TRADITIONAL SECURITY LIGHT								
49WJ25	55	5,772	105	120-277	75	5000K	16"x16" x6.5"	250W MH
49WJ26	81	8,436	104	120-277	76	5000K	16"x16" x6.5"	320W PSMH
49WJ27	110	11,319	102	120-277	78	5000K	16"x16" x6.5"	400W HID



LED MEDIUM FLOOD LIGHT

An efficient, energy saving replacement for metal halide and high-pressure sodium fixtures, containing an integral listed driver, the LED Flood Light Series fixtures can be easily installed to a slip fitter.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED TRADITIONAL SECURITY LIGHT								
49WJ19	55	5,772	105	120-277	75	5000K	16"x16" x6.5"	250W MH
49WJ20	81	8,436	104	120-277	76	5000K	16"x16" x6.5"	320W PSMH
49WJ21	110	11,319	102	120-277	78	5000K	16"x16" x6.5"	400W HID



LED BARN LIGHT

The LED Barn Light with prismatic lens replicate the form and function of 150 watt high-pressure sodium or 175-watt metal halide fixtures, while using just 35 and 45 watts, respectively.

SKU NO.	WATTS	LUMENS	EFFICACY	VOLTAGE	CRI	CCT	(H"XW"XD")	EQUIV.
LED ROUND PENDANT HIGH BAY								
53DK17	34	3,327	99	120-277	78	5000K	7.67"x9.50" x14.76"	150W HPS

