

LED OMNIDIRECTIONAL A-LAMP
A19 NON-DIM SERIES



6W & 9W



11W & 14W



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescents that produces even light in all directions. They are suited to a wide variety of residential and commercial applications, pendants, wall sconces and table and floor lamps.

FEATURES:

- 6 Watts (40W Equivalent, 480 Lumens)
- 9 Watts (60W Equivalent, 800 Lumens)
- 11 Watts (75W Equivalent, 1100 Lumens)
- 14 Watts (100W Equivalent, 1600 Lumens)
- 15,000 hour life (L70 standards)
- CCT: 2700K & 3000K Standard (4000K & 5000K, special order only. Please call MaxLite for more information.)
- CRI: ≥ 80
- Non-Dimmable
- Saves more than 84 percent on energy
- Power factor: ≥ 0.6
- Standard E26 base
- Mercury-free
- RoHS Compliant
- Three year limited warranty
- ENERGY STAR pending (14A19ND30 - End of December)

APPLICATIONS

- Table and floor lamps
- Sconces
- Not for use in fully enclosed luminaires
- Suitable for use in damp locations

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 11A19ND27	
FAMILY	BASE	DIMMABILITY	CCT
6A19= 6 watts, A19 9A19= 9 watts, A19 11A19= 11 watts, A19 14A19= 14 watts, A19	(OMIT)= E26	ND= Non-Dimmable	27= 2700K 30= 3000K

NOTES:

1. Available in 4-Pack is item 9A19ND27/4P
2. 11A19ND30 is not ENERGY STAR certified

SPECIFICATIONS:

		6A19NDxx	9A19NDxx	11A19NDxx	14A19NDxx
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption	6W	9W	11W	14W
	Lumens Delivered	480	800	1,100	1,600
	Efficacy (lm/w)	80	89	100	114
	CRI	≥82			
	Color Temperature (CCT)	2700K, 3000K (4000K & 5000K special order only, contact MaxLite for more information)			
	Lumen Maintenance (L70)	15,000 Hours			
	Dimmable	No			
ELECTRICAL	Power Factor	≥0.6			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Environment	Dry, Damp			
	Warranty	3 Year Limited			

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL NUMBER	ENERGY STAR	INPUT WATTAGE	EQUIVALENT WATTAGE	DELIVERED LUMENS	EFFICACY (LM/W)	CRI	CCT (K)	DIMENSIONS (D" x MOL")
E26 Base									
102327	6A19ND27	★	6	40W Inc.	480	80	82	2700K	2.36" x 4.40"
102328	6A19ND30	★	6	40W Inc.	480	80	82	3000K	
102329	9A19ND27	★	9	60W Inc.	800	89	82	2700K	
102384	9A19ND27/4P (4-Pack)	★	9	60W Inc.	800	89	82	2700K	
102330	9A19ND30	★	9	60W Inc.	800	89	82	3000K	
102331	11A19ND27	★	11	75W Inc.	1100	100	82	2700K	2.48" x 4.40"
102332	11A19ND30		11	75W Inc.	1100	100	82	3000K	
102333	14A19ND27	★	14	100W Inc.	1600	114	82	2700K	
102334	14A19ND30	☆	14	100W Inc.	1600	114	82	3000K	

★ ENERGY STAR Certified
☆ ENERGY STAR Pending

Specifications are subject to change without notice.