

**LED PUCK LAMP**  
E26 & GU24 SERIES



**E26/GU24**  
9W Dim & 10W Non-Dim



**E26/GU24**  
10W Compact Non-Dim  
UL Listed (Wet) @ 120V & 277V

**PRODUCT DESCRIPTION:**

MaxLite's LED Puck Lamp is a leading edge energy efficient light source suitable for use in a wide variety of luminaires.

The puck lamp was designed with a proprietary heatsink which minimizes thermal levels allowing this light source to be used in totally enclosed luminaires.

The puck lamp is fully dimmable (9W only) and emits light equivalent to a 60W incandescent lamp.

**FEATURES:**

- 9W UL Listed (Wet) @ 120V
- 10W UL Listed (Wet) @ 120V & 277V
- Dimmable (9W only), Non-Dimmable (10W)
- Suitable for totally enclosed luminaires
- Fits into same fixtures where Squat CFLs are used, allows cooler and longer-lasting fixture life
- Light output equivalent to a 60W A lamp
- This device is not intended for use with emergency exits

**APPLICATIONS:**

- Closet light
- Ceiling fan
- Pendants
- Downlights
- Track lights
- Coach lights
- Outdoor Sconces

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 9PUAGUDLED27	
FAMILY DESCRIPTION		CCT	
<b>9PUADLED=</b>	9W Puck Lamp, E26 Base, Dimmable (60W equivalent)	<b>27=</b>	2700K
<b>9PUAGUDLED=</b>	9W Puck Lamp, GU24 Base, Dimmable (60W equivalent)	<b>30=</b>	3000K
<b>10PUALED=</b>	10W Puck Lamp, E26 Base, Non-Dimmable (60W equivalent)		
<b>10PUAGULED=</b>	10W Puck Lamp, GU24 Base, Non-Dimmable (60W equivalent)		

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 10CPUAGULED30	
FAMILY DESCRIPTION		CCT	
<b>10CPUALED=</b>	10W Puck Lamp, E26 Base, Non-Dimmable (60W equivalent)	<b>27=</b>	2700K
<b>10CPUAGULED=</b>	10W Puck Lamp, GU24 Base, Non-Dimmable (60W equivalent)	<b>30=</b>	3000K

**SPECIFICATIONS:**

ITEM	SPECIFICATION	9W DIM	10W NON-DIM	10W COMPACT NON-DIM
		DETAILS		
GENERAL PERFORMANCE	Power Consumption (W)	9	10	10
	Efficacy (lm/W)	89-94	85-90	90-100
	Lumens Delivered (lm)	800	850-900	900-1000
	Color Temperature	2700K, 3000K		
	CRI	≥ 80		
	L70 Lifetime (hours)	25,000		
ELECTRICAL	Input Voltage	120V	120-277V	
	Power Factor	≥0.90	≥0.90 (120V), ≥0.80 (277V)	
PHYSICAL	Operating Temperature	-4°F to 104°F		
CERTIFICATION	Environment	Wet (120V)	Wet (120V & 277V)	
	Certification	cULus, LM-79, LM-80		
	Material Usage	RoHS compliant; no mercury		
	Warranty	5 years		

**ORDERING:**

ORDER CODE	WATTS (NOMINAL)	MODEL	BASE TYPE	DIMMABLE	DELIVERED LUMENS	LIFE HOURS (L70)	DIMENSIONS (H" x D")	CCT
<b>NON COMPACT MODELS</b>								
76899	9	9PUADLED27	E26	Yes	800	25,000	2.94" x 2.98"	2700K
76900	9	9PUADLED30	E26	Yes	850	25,000	2.94" x 2.98"	3000K
76901	9	9PUAGUDLED27	GU24	Yes	800	25,000	2.35" x 2.98"	2700K
76902	9	9PUAGUDLED30	GU24	Yes	850	25,000	2.35" x 2.98"	3000K
76903	10	10PUALED27	E26	No	850	25,000	2.94" x 2.98"	2700K
76904	10	10PUALED30	E26	No	900	25,000	2.94" x 2.98"	3000K
76905	10	10PUAGULED27	GU24	No	850	25,000	2.35" x 2.98"	2700K
76906	10	10PUAGULED30	GU24	No	900	25,000	2.35" x 2.98"	3000K
<b>COMPACT MODELS</b>								
76907	10	10CPUALED27	E26	No	900	25,000	2.97" x 2.47"	2700K
76908	10	10CPUALED30	E26	No	1000	25,000	2.97" x 2.47"	3000K
76909	10	10CPUAGULED27	GU24	No	900	25,000	2.36" x 2.47"	2700K
76910	10	10CPUAGULED30	GU24	No	1000	25,000	2.36" x 2.47"	3000K

**COMPATIBLE DIMMERS:**

MAKE	DIMMER MODEL	MAKE	DIMMER MODEL
Lutron	CTCL-153P	Leviton	IPL06
Lutron	DVCL-153P	Leviton	IP110
Lutron	LGCL-153P	Leviton	6631-LW
Lutron	S-600	Leviton	6683-IW