

**HIGH TEMPERATURE
ROUND HIGH BAY
HPH SERIES**



PRODUCT DESCRIPTION:


The HPH Series Pendant is specifically designed to provide reliable illumination in industrial locations with high ceilings and high ambient operating temperatures up to 60° C, such as steel mills, heavy manufacturing plants and hangars. A superior thermal management system ensures consistent light levels and exceptional efficacy of 130 lm/W in hot environments. The fixture is IP66 rated and wet location listed to withstand wash downs and protect against the ingress of dust, oil and other non-corrosive materials.

FEATURES:

- Five years limited warranty/ with option for 10 year
- 0-10V dimming standard
- Power factor >0.9
- Universal voltage 120-277V and 347-480V
- Beam Angle 120°
- L70 lumen maintenance of 50,000 hours
- L90 lumen maintenance of 36,000 hours
- Operating temperature: -40°F to 140°F (-40°C to 60°C)
- Operating humidity 10% to 80% RH

CONSTRUCTION:

- Housing is cold forge Aluminum heat sink for High Ambient Temperature
- Gasket clear glass lens for IP66 Rating
- Isolated driver compartment



MODEL SELECTION		Typical order example: HPH240UC-50					
HPH	240		C	-	50		
FAMILY	WATTAGE	VOLTAGE	LENS	-	CCT	OPTIONS	OPTIONS
HPH= High Bay Pendant High Ambient	240= 240W	U= 100-277V H= 200-480V*	C= Clear	-	40= 4000K 50= 5000K	(Omit)= None MSV= Bi-Level Motion Sensor	(Omit)= None C1= Cord and Plug 120V C2= Cord and Plug 277V


* High voltage option is special order

SPECIFICATIONS:

HPH240UC-50

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Power Consumption (W)	240W
	Lumens Delivered (lm)	31,200
	Efficacy (lm/W)	130
	CRI	≥80
	Color Temperature (K)	4000K, 5000K
	L70 Lumen maintenance (hours)	50,000
	Color Consistency	Proprietary binning for uniform color
ELECTRICAL	Power Factor	>0.9
	Input Voltage	100-277V (200-480V Optional)
	Dimming	0-10V, to 10%
PHYSICAL	Mounting	Hook standard
	Operating Temperature	-40°F to 140°F (60°C)
	Humidity	10-90% RH, non-condensing
QUALIFICATION	Qualification	IP66, cULus, FCC, DLC Premium
	Material Usage	RoHS compliant; no mercury
	Environment	Indoor / Wet
	Warranty	5 Years

* All specifications are preliminary and subject to change

SENSOR OPTION	TECHNOLOGY	DIMMING	DAYLIGHT HARVESTING	REMOTE CONTROL	QR CODE
MSV	PIR	Bi-Level	Set Point	Yes	

* For motion sensor settings and information, please visit www.maxlite.com/controls