

**SLIM CEILING FLUSH MOUNT**  
ML2L SERIES-LED INTEGRATED



**PRODUCT DESCRIPTION:**

The LED Slim Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for homes, hotels, motels and commercial properties. Built with an integrated LED panel, MaxLite slim flush mounts produce a high quality of light with superior longevity and energy savings when compared to traditional sources. The series is available in brushed nickel or white finishes with a high-transmission glass lens to complement virtually any décor.

**FEATURES:**

- Multiple sizes and wattages available
- Triac dimming
- Suitable for damp locations
- Dedicated Voltage: 120V
- CRI: ≥80
- 5 year warranty



MODEL SELECTION (Full list of order codes on pg. 1)

Typical order example: ML2L13SLNI1530

ML2L		SL			
FAMILY	SIZE	SLIM STYLE	FINISH	WATTAGE	CCT
ML2L= Flush Mount	11= 11" 13= 13" 15= 15"	SL= Slim	NI = Nickel WH= White	12= 12W 15= 15W 24= 24W	30= 3000K

**ORDERING:**

ORDER CODE	MODEL NUMBER	DESCRIPTION
1410130	ML2L11SLNI1230	SLIM FLUSH MOUNT 11" 12W 3000K BRUSHED NICKEL
1410206	ML2L11SLWH1230	SLIM FLUSH MOUNT 11" 12W 3000K WHITE
1410132	ML2L13SLNI1530	SLIM FLUSH MOUNT 13" 15W 3000K BRUSHED NICKEL
1410210	ML2L13SLWH1530	SLIM FLUSH MOUNT 13" 15W 3000K WHITE
1410134	ML2L15SLNI2430	SLIM FLUSH MOUNT 15" 24W 3000K BRUSHED NICKEL
1410214	ML2L15SLWH2430	SLIM FLUSH MOUNT 15" 24W 3000K WHITE

\*Please contact your MaxLite representative to order products that don't have order codes listed here.

**SPECIFICATIONS:**

SPECIFICATIONS:		ML2L11SLNI12XX	ML2L13SLNI15XX	ML2L15SLNI24XX
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Power Consumption (W)	12W	15W	24W
	Lumens Delivered (lm)	875	1,054	1,650lm
	Efficacy (lm/W)	70.4	70.3	68.8
	CRI	80		
	Color Temperature (K)	3000K		
	L70 Lifetime (Hours)	50,000 hrs		
	Color Consistency	Proprietary binning for uniform color		
ELECTRICAL	Power Factor	0.9		
	Input Voltage	120V		
	Input Frequency	60Hz		
PHYSICAL	Operating Temperature	-4°F to 104°F (-20°C to 40°C)		
	Dimensions	11.0"D x 1"H	13.0"D x 1"H	14.9"D x 1"H
QUALIFICATION	Qualification	Energy Star, UL, FCC		
	Material Usage	RoHS Compliant, no mercury		
	Environment	Suitable for damp locations		
	Warranty	5 Years		

Lighting layouts and spacing criteria available upon request

**COMPATIBLE DIMMERS:**

MANUFACTURE	DIMMER MODEL
LUTRON	CTCL-153P
	TV-600P
	S-600P
	LG-600P
	TG-600PH-WH

MANUFACTURE	DIMMER MODEL
LEVITON	RTD1-10X