

## CEILING FLUSH MOUNT

### ML2LA SERIES - LED INTEGRATED



PUFF



ARCHITECTURAL



TRADITIONAL



PEARL



### PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. Built with an integrated LED panel, MaxLite flush mounts produce a high quality of light with superior longevity and energy savings when compared to traditional sources. The series is available in nickel, white or bronze finishes with a high-transmission glass lens to complement virtually any décor.

### FEATURES:

- ETL listed for damp locations
- Voltage / Frequency: 120V, Triac Dimming, 60 Hz
- CRI: ≥80 or ≥90 available
- Operating temperature: -4°F to 104°F (-20°C to 40°C)
- Rated Life: L70 >= 50,000 HOURS
- Construction: Die formed steel
- Warranty: 5 Years
- Powder coat finish

## PUFF



WATTAGE	18W	24W
Sourced lumen (lm @ 2700k, 80CRI)	1440	1950
Efficacy (lm/W @ 2700k, 80CRI)	80	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1408691	ML2LAMPWH18827
100703	ML2LALPWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATT-AGE	CRI	CCT	OPTIONS
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 4.0 "H	P= Puff	WH= White	[BLANK]= 120V Triac dimming	18= 18W	8= 80CRI 9= 90CRI*	27= 2700K 30= 3000K	J= JA8 Compliant <sup>2</sup>
		L= Large, 16"D x 42"H				24= 24W			

<sup>1</sup> Consult factory for lead times and order quantities

<sup>2</sup> JA8 compliance available in 90CRI, 14W, 11"D x 3.15"H model only. Consult factory for lead time and order quantities.

**ARCHITECTURAL**



WATTAGE	22W	24W
Sourced lumen (lm @ 2700k, 80CRI)	1600	1950
Efficacy (lm/W @ 2700k, 80CRI)	73	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1410232	ML2LAMABN22830
1409612	ML2LALABN24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 14.2" D x 3.5"H	A= Architectural	BN= Brushed Nickel	[BLANK]= 120V Triac dimming	22= 22W	8= 80CRI 9= 90CRI*	27= 2700K
		L= Large, 14.2"D x 3.5"H				24= 24W		30= 3000K

<sup>1</sup> Consult factory for lead times and order quantities

**TRADITIONAL**



WATTAGE	18W	24W
Sourced lumen (lm @ 2700k, 80CRI)	1260	1650
Efficacy (lm/W @ 2700k, 80CRI)	70	69

MADE TO ORDER	
ORDER CODE	CATALOG NUMBER
1409610	ML2LAMTRWH18830
1409609	ML2LALTRWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 5.1"H	TR Traditional	WH= White	[BLANK]= 120V Triac dimming	18= 18W	8= 80CRI 9= 90CRI*	27= 2700K
		L= Large, 15"D x 5.2"H				24= 24W		30= 3000K

<sup>1</sup> Consult factory for lead times and order quantities

**PEARL**



WATTAGE	16W	24W
Sourced lumen (lm @ 2700k, 80CRI)	1100	1350
Efficacy (lm/W @ 2700k, 80CRI)	69	61

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1408700	ML2LAMPBRN16827
1408701	ML2LALPRBN22827

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2= Ceiling Flush Mounts	LA= LED Integrated	M= Medium, 13" D x 4.2"H	PR=	BN= Brushed Nickel	[BLANK]= 120V Triac dimming	16= 16W	8= 80CRI 9= 90CRI*	27= 2700K
		L= Large, 15"D x 4.6"H				22= 22W		30= 3000K

<sup>1</sup> Consult factory for lead times and order quantities