

OUTDOOR LANTERN
ML4 SERIES - LED INTEGRATED



TRADITIONAL



MISSION



COACH



RANCH

PRODUCT DESCRIPTION:

MaxLite LED Lanterns provide long-lasting illumination and energy cost savings for multi-residential properties. BULB in the Box as well as LED integrated solutions are readily available and provide excellent and uniform light quality.

FEATURES:

- Dusk to Dawn available

APPLICATIONS:

- Residential
- Hotel/Motel
- Property Management

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

MODEL SELECTION (Full list of order codes on pg. 2 & 3)

Typical order example: ML4LS14SOLB

ORDER CODE	MODEL NUMBER	STYLE	WATTAGE	FINISH	CCT	CONTROLS
97868	ML4LS10MCLBK827	Coach	10W, 60 inc replacement	Black	80 CRI, 2700K	None
96974	ML4LS12SRLBK827	Ranch	12W, 60 inc			
101444	ML4LS14SOLBPC	Traditional	14W, 60 inc replacement			Dusk to dawn
1408707	ML4LASMSB14827PC	Mission				

SPECIFICATIONS:

		ML4LASMSB14827PC	ML4LS14SOLBPC	ML4LS10MCLBK827	ML4LS12SRLBK827
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption (W)	14W	14W	10W	12.5W
	Delivered Lumens	813 lm	1,166 lm	500 lm	750 lm
	Efficacy (lm/W)	58.1 lm/W	86 lm/W	50 lm/W	62.1 lm/W
	L70 Lumen Maintenance	> 50,000 hours			
	Spacing Criteria	Contact MaxLite for Installation Criteria			
	Dimming	Triac Dimming	Non Dimmable		
ELECTRICAL	Input Voltage	120V, 60Hz	120V, 50-60 Hz	120V, 60 Hz	120V, 50-60 Hz
	Power Factor	≥0.9			
PHYSICAL	Housing	DieCast Al	Metal Casting	Aluminum casting	Die Cast Aluminum
	Lens	PC Frosted	PC	Crackle Glass	Plastic
	Dimensions (L x W x H)	7.9"L x 4.3"W x 9.8"H	7.5"L x 4"W x 9.75"H	6.5 "L X 9.0" W X 13.75"H	6.7"L x 4.5" W X10.25"H
	Finish	Black			
	Operating Temperature	-4°F to 104°F (-20°C - 40°C)		-4°F-113°F (-20°C-45°C)	
	Mounting	Cross Bar onto Junction Box			
CERTIFICATION	Environment	Suitable for Wet Locations		Suitable for damp locations,Class 2 power supply	
	Certification	Energy Star, ETL, FCC		Energy Star, UL, FCC	
	Warranty	5 year warranty*			