

OUTDOOR LANTERN- LED INTEGRATED
ML4LS14SOLBxx



PRODUCT DESCRIPTION:

This Outdoor LED Lantern is a wall mounted residential lighting product. Optional photocell integrated into the product allows for greater energy savings when in the presence of daylight. These integrated LED products offer higher efficiency and longer lifetime than fluorescent equivalents, reducing the amount of maintenance required.

FEATURES:

- Optional integrated dusk to dawn photocell sensor
- Dedicated voltage: 120V
- CRI: ≥80
- Power Factor: ≥90
- Operating Temperature: -4°F to 113°F (-20°C - 45°C)
- L70 lumen maintenance 50,000 hours
- Non-dimmable

CONSTRUCTIONS:

- Die-cast aluminum housing with powder coated paint
- Frosted PC lens
- Black finish standard

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

ORDERING*:

ORDER CODE	MODEL	DESCRIPTION	WATTAGE	CCT
101488	ML4LS14SOLB	OUTDOOR FIXTURE 14W LED LSD SMALL LANTERN 2700K BLACK FINISH >80CRI PLASTIC DIFFUSER	14W	2700K
101444	ML4LS14SOLBPC	OUTDOOR FIXTURE 14W LED SMALL LANTERN 2700K BLACK FINISH >80CRI PLASTIC DIFFUSER W/ PHOTOCCELL	14W	2700K

*Please contact your MaxLite representative to order products that don't have order codes listed here.

SPECIFICATIONS:

ML4LS14SOLB

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Spacing Criteria	Contact MaxLite for Installation Criteria
	Color Temperature (CCT)	2700K
	Delivered Lumens	1,166 lm
	Efficacy (lm/W)	86 lm/W
	Dimming	Non Dimmable
ELECTRICAL	Input Voltage	120V, 50-60 Hz
	Driver Input Current (mA)	.09 A Max.
	Power Consumption	14W
PHYSICAL	Dimensions (L x W x H)	7.5"L x 4"W x 9.75"H
	Weight	1.52 lbs
	Housing	Metal Casting
	Lens	PC
	Mounting	Cross Bar Onto Junction Box
	Operating Temperature	-4°F-113°F (-20°C-45°C)
CERTIFICATION	Certification	FCC, ETL, ES
	Environment	Suitable for wet locations
	Warranty	5 year warranty*