

**VANITY BAR**  
ML8 SERIES - BULB IN BOX



**PRODUCT DESCRIPTION:**

LED Vanity Bar provides long-lasting, even illumination for both residential and commercial property applications. Available in 2ft, the Vanity Bar is constructed with a high transmission glass diffuser and is available in nickel, white, or dark bronze finish. This bulb in a box solution comes prepackaged with JA8 compliant E26 based LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

**FEATURES:**

- CRI: ≥90
- JA8 compliant flicker free bulb included (E26 Base)
- Dedicated Voltage: 120V, 60Hz
- Five year limited warranty
- Triac dimming standard
- Operating Temperature: 0°F to 104°F

**CONSTRUCTIONS:**

- Formed steel
- Powder coat finish
- Glass Tulip Shade



**ORDERING:**

| ORDER CODE | MODEL#        | ITEM DESCRIPTION   |
|------------|---------------|--|
| 1408625    | ML8E303TUNI27 | VANITY BAR TULIP NICKEL FINISH WITH 3X10W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP      |
| 1408626    | ML8E303TUWH27 | VANITY BAR TULIP WHITE FINISH WITH 3X10W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP       |
| 1408627    | ML8E303TUBZ27 | VANITY BAR TULIP DARK BRONZE FINISH WITH 3X10W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP |

**SPECIFICATIONS:**

|                            |                        | ML8E303TUNI27                    | ML8E303TUWH27 | ML8E303TUBZ27 |
|----------------------------|------------------------|----------------------------------|---------------|---------------|
| ITEM                       | SPECIFICATION          |                                  |               |               |
| <b>GENERAL PERFORMANCE</b> | Power Consumption (W)  | 30 (3 x 10)                      | 30 (3 x 10)   | 30 (3 x 10)   |
|                            | Source Lumens          | 2,400                            | 2,400         | 2,400         |
|                            | Efficacy (lm/W)        | 80                               | 80            | 80            |
|                            | Color Temperature (K)  | 2700K                            |               |               |
|                            | CRI                    | ≥90                              |               |               |
|                            | L70 Lumen Maintenance  | 25,000 hours                     |               |               |
| <b>ELECTRICAL</b>          | Input Voltage          | 120V                             |               |               |
|                            | Input Frequency        | 60Hz                             |               |               |
|                            | Power Factor           | ≥0.9                             |               |               |
| <b>PHYSICAL</b>            | Dimensions (L x W x H) | 23" x 10" x 9"                   |               |               |
|                            | Finish                 | Brushed Nickel, White, or Bronze |               |               |
|                            | Operating Temperature  | 0°F to 104°F                     |               |               |
| <b>CERTIFICATION</b>       | Environment            | Suitable for Damp Locations      |               |               |
|                            | Certification          | Energy Star, cETLus, FCC         |               |               |
|                            | Warranty               | 5 year limited warranty          |               |               |