



## LM-79-08 Test Report

for

### Maxlite Inc.

12 York Ave West Caldwell NJ 07006

### LED Flush Mount

**Model: ML2LA23LTNBNI927**

### Laboratory: Leading Testing Laboratories

**NVLAP CODE: 200960-0**

No.1805, DongLiu road, BinJiang District, Hangzhou, China

Tel: +86-571-56680806

www.ledtestlab.com

Report No.: HZ15040022af

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:

Engineer: April Zou  
May 19, 2015

Approved by:



Manager: Jim Zhang  
May 19, 2015

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government

## Test Summary

Sample Tested: **ML2LA23LTNBNI927**

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
60.9	1469.0	24.14	0.9859
CCT (K)	CRI	Stabilization Time (Light & Power)	
2753	90.4	65	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

### Test specifications:

**Date of Receipt** : Apr. 27, 2015

**Date of Test** : May 13, 2015

**Test item** : Total Luminous Flux, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters

**Reference Standard** : IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products

## TABLE OF CONTENT

LM-79-08 Test Report.....	1
Test Summary.....	1
Sample Photo.....	4
TEST RESULTS .....	5
Spectral Power Distribution - Sphere Spectroradiometer Method .....	6
Chromaticity Diagram - Sphere Spectroradiometer Method.....	7
Nominal CCT Quadrangles – Sphere Spectroradiometer Method .....	8
EQUIPMENT LIST .....	9
TEST METHODS .....	9
Seasoning of SSL Product.....	9
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	9

## Sample Photo



Sample view

### Equipment Under Test (EUT)

<b>Name</b>	: LED Flush Mount
<b>Model</b>	: ML2LA23LTNBNI927
<b>Electrical Ratings</b>	: 120Vac, 50/60Hz, 23W
<b>Product Description</b>	: 2700K, Dimmable, CRI90, Frosted Glass Cover Model of LED light source: Luxeon 3030 2D Manufacturer of light source: Philips Quantity LED light source: 46PCS
<b>Manufacturer</b>	: Maxlite Inc.
<b>Address</b>	: 12 York Ave West Caldwell NJ07006

## TEST RESULTS

Test ambient temperature was 24.8°C.

Test orientation was Light down. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 65 minutes, and the total operating time including stabilization was 70 minutes.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.204
Power Factor	0.9859
Test Power (W)	24.14
THD A%	16.63
Luminous Efficacy (lm/W)	60.9
Total Luminous Flux (lm)	1469.0
Color Rendering Index (CRI)	90.4
R9	47.3
Correlated Color Temperature (CCT)(K)	2753
Chromaticity Chroma x	0.4576
Chromaticity Chroma y	0.4135
Chromaticity Chroma u	0.2597
Chromaticity Chroma v	0.3521
Duv	0.0011
Chromaticity Chroma u'	0.2597
Chromaticity Chroma v'	0.5281

Special Color Rendering Indices	
R1	89.9
R2	95.4
R3	98.9
R4	89.3
R5	89.5
R6	95
R7	89.6
R8	75.8
R9	47.3
R10	88.5
R11	89.6
R12	80.5
R13	91.3
R14	99.2

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u',v') diagram,  $u' = u = 4x/(-2x+12y+3)$ ,  $v' = 3v/2 = 9y/(-2x+12y+3)$ .

### Spectral Power Distribution - Sphere Spectroradiometer Method





Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	1.10E-04	485	6.81E-03	590	2.66E-02	695	1.07E-02
385	1.22E-04	490	7.48E-03	595	2.78E-02	700	9.42E-03
390	1.31E-04	495	8.35E-03	600	2.88E-02	705	8.25E-03
395	1.39E-04	500	9.48E-03	605	2.98E-02	710	7.19E-03
400	1.53E-04	505	1.06E-02	610	3.06E-02	715	6.28E-03
405	1.81E-04	510	1.17E-02	615	3.09E-02	720	5.45E-03
410	2.49E-04	515	1.26E-02	620	3.10E-02	725	4.73E-03
415	3.61E-04	520	1.35E-02	625	3.07E-02	730	4.07E-03
420	5.58E-04	525	1.43E-02	630	3.02E-02	735	3.50E-03
425	8.69E-04	530	1.51E-02	635	2.94E-02	740	3.00E-03
430	1.38E-03	535	1.58E-02	640	2.83E-02	745	2.57E-03
435	2.17E-03	540	1.66E-02	645	2.68E-02	750	2.20E-03
440	3.61E-03	545	1.75E-02	650	2.54E-02	755	1.88E-03
445	6.32E-03	550	1.82E-02	655	2.38E-02	760	1.63E-03
450	9.78E-03	555	1.91E-02	660	2.21E-02	765	1.38E-03
455	1.07E-02	560	2.00E-02	665	2.03E-02	770	1.17E-03
460	9.30E-03	565	2.09E-02	670	1.85E-02	775	1.00E-03
465	8.40E-03	570	2.20E-02	675	1.68E-02	780	8.70E-04
470	7.59E-03	575	2.31E-02	680	1.52E-02		
475	6.69E-03	580	2.42E-02	685	1.35E-02		
480	6.43E-03	585	2.55E-02	690	1.21E-02		

Table 3: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

### Chromaticity Diagram - Sphere Spectroradiometer Method



Tristimulus values(x, y) : (0.4576, 0.4135)

Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

**Nominal CCT Quadrangles – Sphere Spectroradiometer Method**




Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram



## EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Integrate Sphere system	2M	HZTE015-01	Sep. 18, 2014	Sep. 17, 2015
Digital Power Meter	WT210	HZTE008-01	Sep. 18, 2014	Sep. 17, 2015
AC Power Supply	PCR 500L	HZTE001-07	Sep. 18, 2014	Sep. 17, 2015
DC Power Supply	6154	HZTE004-04	Sep. 18, 2014	Sep. 17, 2015
Temperature and humidity recorder	JR900	HZTE018-01	Sep. 18, 2014	Sep. 17, 2015
Standard source	SCL-1400	HZTE012-02	Sep. 18, 2014	Sep. 17, 2015

Table 4: Test Equipment List

## TEST METHODS

### Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

### Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is  $4\pi$ . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated LED lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expanded uncertainty is 1.06% with a coverage factor  $k=2$ .

\*\*\* End of Report \*\*\*

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.