

# HazLOC Highbay CID2

HARSH & HAZARDOUS



**80W**  
12,000 lm

**120W**  
18,000 lm

**150W**  
22,500 lm



**200W**  
30,000 lm



## FEATURES:

- 3000K, 4000K, 5000K
- Customizable offering with clear, diffused and drop lens option
- Efficacy up to 150 lm/W

## DIMMING:

- 120-277V option available with 0-10V dimming (10%)
- 347-480V option available with 0-10V dimming (10%)

## CONSTRUCTION:

- Die cast aluminum body and impact resistant tempered glass lens
- Stainless steel exposed fasteners
- High temperature silicone gasketing

## MOUNTINGS:

- Universal mounting for pendant, Yoke Mount, Ceiling, Wall, Stanchion Mount

## LISTINGS:

- Class I, Division 2, Groups A, B, C, D
- Class II, Division 1, Groups E, F, G
- Class II, Division 2, Groups F, G
- Class III, Division 1
- Marine Grade
- 1000 hours salt spray testing
- IK08
- IP66
- FCC
- 5G Vibration rated

FAMILY	WATTAGE	VOLTAGE	DISTRIBUTION	LENS	CCT	MOUNTING	FINISH
HLRM= Medium Size Round, CID2	80= 80W 120= 210W 150= 150W 200= 200W	U= 120-277V H= 347-480V	[Blank]= Wide, 110°	[Blank]= Clear Glass D= Diffused Glass L= Low Bay/Drop Lens	[BLANK]= 5000K 40= 4000K 30= 3000K	[Blank]= Universal, Ceiling and Pendant	[Blank]= Grey