

# MaxLite® Slim Flood Lights



**Good Things Come In Small Packages!**



**15W**  
1,590-1,635 lm



**29W**  
3,400-3,430 lm



**50W**  
5,800-6,270 lm



**70W**  
8,480-9,980 lm



**Photocell Receptacle**



**CCT Selectable Button**

**90W**  
11,320-13,180 lm



- 4 slim profile housings with 5 wattages tailored for each of your applications
- 3 mountings to handle all your different installation needs
- 3 CCTs, 70W & 90W are CCT selectable
- 3-pin twist lock receptacle with shorting cap standard for 70W & 90W

FAMILY	WATTAGE	VOLTAGE	DISTRIBUTION	CCT	FINISH	MOUNTING	OPTIONS
MSF= Slim Flood	15= 15W 29= 29W 50= 50W	U= 120-277V	N= Narrow <i>(Available in 50W only)</i>  W= Wide	30= 3000K 40= 4000K 50= 5000K	B= Bronze <i>(Contact MaxLite for additional finishes)</i>	KT= Knuckle with 1/2" Thread SK= Slipfitter Knuckle Y= yoke	RPC= 3 pin NEMA Photocell Receptacle with Shorting Cap <i>(Included and only available with 70W &amp; 90W)</i>
	70= 70W 90= 90W			CS= CCT Selectable (3K, 4K, 5K) <i>(Available in 70W &amp; 90W only)</i>			