

MaxLite® Commercial Downlights RCF Series



CCT Selectable
120-277V, Triac Dimming at 120V

CCT & Wattage Selectable
120-347V, 0-10V Dimming



4" **6"** **6"** **8"** **8"** **8"** **9.5"**
9W | **13W** | **18W** | **13W** | **18W** | **22W** | **40W**
 750 lm | 1,100 lm | 1,650 lm | 1,115 lm | 1,650 lm | 2,120 lm | 3,500 lm

4" **6"** **8"** **9.5"**
12W | **10/12/17W** | **14/17/20W** | **30/35/40W**
 900 lm | 1,000/1,200/1,700 lm | 1,400/1,700/2,000 lm | 2,550/2,975/3,400 lm



- CCT 3000K/3500K/4000K Selectable
- Field installable Emergency Battery back up kit optional
- New construction frames optional
- Listed as a fixture and a retrofit
- 4", 6", 8" covers up to the next size. Goof ring not required
- Goof ring available for 9.5" models to achieve a 12" coverage

UNIVERSAL RCF SERIES - CCT SELECTABLE

FAMILY	SIZE	WATTAGE	CCT	VOLTAGE	FINISH
RCF= Recessed Commercial Fixture	4= 4"	09= 9W	CS= CCT Selectable (3K, 35K, 4K)	[BLANK]= 120-277V, Triac Dimming	W= White
	6= 6"	13= 13W			
	8= 8"	18= 18W			
	8= 8"	22= 22W			
	10= 9.5"	40= 40W			

UNIVERSAL RCF SERIES - CCT & WATTAGE SELECTABLE

FAMILY	SIZE	WATTAGE	CCT	VOLTAGE	FINISH
RCF= Recessed Commercial Fixture	4= 4"	12= 12W	CS= CCT Selectable (3K, 35K, 4K)	D= 120-347V, 0-10V Dimming	W= White
	6= 6"	10W= 10/12/17W			
	8= 8"	14W= 14/17/20W			
	10= 9.5"	30W= 30/35/40W			