

# MaxLite® Slim Downlights



4" | 6" | 8"  
**13W** | **16W** | **20W**  
 796 lm | 1,126 lm | 1,520 lm



4" | 6" | 8"  
**13W** | **16W** | **20W**  
 836 lm | 1,126 lm | 1,516 lm



4" | 6" | 8"  
**12W** | **12W** | **18W**  
 800 lm | 900 lm | 1,500 lm



The CCT Selectable Slim Downlight mounts directly into the ceiling - no recessed can required! With a simple flick of a switch (located on the remote driver junction box), installers can choose the color temperature that best suits their application need.

- CCT Selectable
- 120V, Triac Dimming
- Beam Angle: ~110°
- New construction rough in template - frames available
- Field installable Emergency Battery Backup
- IC Rated
- Airtight

FAMILY	SHAPE	SIZE	WATTAGE	CCT	TRIM	CRI/JAB
SDL= Slim Downlight Series Flush Style	R= Round S= Square	4= 4"	13= 13W	CS= 90 CRI, 2700K/3000K/3500K/4000K/5000K	W= White	J= 90 CRI; T24-JA8-2016 Compliant
		6= 6"	16= 16W			
		8= 8"	20= 20W			

FAMILY	SHAPE	SIZE	WATTAGE	CRI+ COLOR SELECTABLE	TRIM
SDB= Slim Downlight Series Baffle Style	R= Round	4= 4"	12= 12W 18= 18W	9CS= 90 CRI, 2700K/3000K/3500K/4000K/5000K	W= White
		6= 6"			
		8= 8"			