

MaxLite® WallMax™ Open Face Wall Packs



CCT Switch



Wattage Switch

28W
3,300 lm

40W
4,700 lm

55W
6,400 lm

80W
9,600 lm

120W
14,000 lm



FEATURES:

- CCT selectable between 3000K, 4000K or 5000K
- Controls Ready - simple plug and play Sensor Receptacle/Socket enables installation of c-Max control nodes without changing the fixture
- High Voltage Option: 277-480V
- Battery Backup Options - 0°C and -20°C
- Avi-On Network Controls Option available
- CRI: ≥80

CONSTRUCTION:

- Rugged die cast housing with corrosion resistant polyester powder paint finish
- Impact resistant borosilicate glass
- Covers old HID footprints (14" and 18")
- 4 x 1/2" conduit holes, one on each side for surface conduit applications

FAMILY	WATTAGE	VOLTAGE	CCT	COLOR	CONTROL OPTIONS	EM OPTIONS
WPOP= WallMax Open Face Wall Pack	28= 28W 40= 40W 55= 55W 80= 80W 120= 120W	U= Universal 120-277V H= High Voltage 277-480V	CS= CCT Selectable (3K, 4K, 5K) WCS= Wattage & CCT Selectable (3K, 4K, 5K) <i>WCS available in 55W (28/40/55W) and 120W (80/100/120W)</i>	B= Dark Bronze <i>(Contact MaxLite for additional finishes)</i>	AV= Avi-On Network Controls CR= Controls Ready receptacle compatible with field installable c-Max control nodes sold separately	BLANK= None EM0= Battery Backup 0°C EM2= Battery Backup -20°C