





Sensor/  
Photocell



CCT Select  
Switch



Round Dome  
Type V



Square  
Type V

MULTIPLE FORM FACTORS:  
ROUND, SQUARE

MULTIPLE LENGTHS : 42", 36"

VANDAL RESISTANT SCREWS

FIELD REPLACEABLE HEADS  
AND SHAFT



Round Dome  
Louver



Round Flat  
Louver



Round Flat  
Type V

**22W**  
2,860 lm



The PathMAX™ Slim LED Bollards offer a modular design with field selectable color temperatures (3000K, 4000K, 5000K) that simplify the product choice for distributors and contractors. Available in round and square silhouettes, the bollards are controls ready and designed with a specialized optics that projects light down and outward for ample illumination on walkways.

FAMILY	SUB FAMILY	SHAPE	STYLE	WATTAGE	VOLTAGE	CCT	DISTRIBUTION	HEIGHT	FINISH	CONTROLS
BL= PathMAX™ Bollard, Slim Series	CL= Classic	R= Round S= Square	D= Dome Top F= Flat Top	22= 22W	U= 120-277V	CS= 3000/ 4000/ 5000K	BLANK= Type V LR= Louvers	BLANK= 42" 36= 36"	B= Bronze Contact Maxlite for custom finishes	<sup>2</sup> CR= Controls Ready

<sup>1</sup>Only available as a Flat Top, Type V distribution, 42" model

<sup>2</sup>Only available with 42" height