

LED Linear High Bay - HL Series (Gen 2)

Uniquely compact and adaptable, the HL Linear High Bay delivers the lumen output of a traditional 600-watt high output fixture in a form factor one-quarter the size. The HL Linear High Bay measures just 14" x 24", comes standard with a wide beam distribution, and has the option for emergency battery backup, various motion sensor options, and numerous mounting options and accessories for optimal function and appearance. Other high bays may offer some of these features, but the HL Linear High Bay accomplishes all of this in a much smaller package.



CUTTING-EDGE OPTICS

High-transmission polycarbonate diffuser delivers exceptional light output with minimal glare, enhancing safety and visual comfort.

PREMIUM APPEARANCE

Slim profile measures less than five inches, for a strikingly clean and unobtrusive aesthetic, while including an integrated sensor.

THERMAL MANAGEMENT

Patent-pending thermal management delivers maximum performance in temperatures up to 50° C.

FIRST, CHOOSE YOUR WATTAGE:

90W

175W EQUIVALENCY
up to 13,300 lm

130W

250W EQUIVALENCY
up to 19,700 lm

160W


400W EQUIVALENCY
up to 24,600 lm

185W

600W EQUIVALENCY
up to 28,500 lm


THEN, CHOOSE YOUR OPTIONS:

VOLTAGE




120-277V COMES STANDARD

LENSES



FROSTED LENS COMES STANDARD

COLOR TEMPS




BATTERY



EM


BATTERY BACKUP

SENSORS



MSC REQUIRES REMOTE

CORDS AND PLUGS



FINALLY, CHOOSE YOUR ACCESSORIES:

WIRE GUARD



SURFACE MOUNT



CABLE KITS



MODULAR WIRING



10' Modular Wiring Drop (120V) OR (277/480V)

MSC SENSOR REMOTE



RETAIL & BIG BOX STORES



AUTO SHOWROOMS



GYMNASIUMS



WAREHOUSES



MANUFACTURING FACILITIES